



Centre Anti-Poison pour le Québec: (800) 463-5060

Tél. (Qc): (418) 660-8666 / 800-890-8666


Fax. (Qc): (418) 660-8998

SAFETY DATA SHEET

SECTION 01 - PRODUCT AND COMPANY IDENTIFICATION

Product Identifier CALCIUM OXIDE		Product Use Laboratory use	
Chemical formula CaO		Product code CP-0116; CR-0117; CR-0985	Molar weight 56,08
Chemical name / Commercial name / Synonymous CALCIUM OXIDE, LIME, CHAUX VIVE, CHAUX BRULÉE, CALX, CALCIA, CALCIUM OXIDE, BURNT LIME, CALX,			
Supplier's name Laboratoire MAT		Address-Street 610, Adanac Street	
City Québec		Province Québec	
Postal code G1C 7B7	Internet www.labmat.com	Phone number 418-660-8666 / 800-890-8666	
Emergency phone	CANUTEC: 613-996-6666 CENTRE ANTI-POISON DU QUÉBEC 800-463-5060		
Date SDS 8/8/2019	SDS Prepared by Laboratoire MAT	E-Mail labmat@labmat.com	

SECTION 02 - HAZARDS IDENTIFICATION

Classification WHIMS / GHS	Skin corrosion/irritation - Skin irritation category 2 Serious eye damage/eye irritation - Serious eye damage category 1 Specific target organ toxicity - Single exposure category 3
Signal Word	DANGER
Hazards statements (H)	H315 Causes skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation.
Precautionary statements (P)	P261 Avoid breathing dust / fume / gas / mist / vapours / spray. P264 Wash the areas of the body that have been in contact with the product after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER or doctor/physician. P312 Call a POISON CENTER or doctor/physician if you feel unwell. P321 Specific treatment (see section 4 of the SDS and on this label). P332 + P313 If skin irritation occurs: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container in accordance with local / regional / national / international regulations or contact a specialist waste disposal company.
PICTOGRAMS	
Other dangers	NFPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Signifiant; 4=Extreme)
	Health 3 Fire 0 Reactivity 1 Special danger

SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingrédients (Dénomination chimique / synonymes)	Numéro CAS et tout identificateur unique	Concentration (%)
Oxyde de calcium	1305-78-8	<=100

SECTION 04 - FIRST AID MEASURES

Eye contact	Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes. If irritation persists, seek medical attention.
Skin contact	Wash skin with plenty of water for at least 15 minutes. Remove soiled clothing. If irritation persists, seek medical attention.
Inhalation	Move the unwell person to the fresh air. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	If the person is conscious, rinse the mouth with water. Never give anything by mouth to an unconscious person. Consult a physician.
Most important symptoms and effects (acute and delayed)	Ref. section 11.
Immediate medical attention and special treatment, if necessary	In case of medical consultation, keep this sheet available.
General advice	Show this safety data sheet to the doctor in attendance.

SECTION 05 - FIREFIGHTING MEASURES

Flammability	No
Ignition conditions	Not flammable or combustible.
Suitable extinguishing media	Dry powder or dry sand.
Unsuitable extinguishing media	Do not use water. Do not use carbon dioxide.
Hazardous combustion / decomposition products	Hazardous decomposition products formed under fire conditions. - Calcium oxide.
Special fire and explosion hazards	Calcium oxide reacts violently with water to generate a lot of heat (risk of explosion in a confined space). This product may react violently with the following products, especially in the presence of heat or moisture: acids, boron oxide + calcium chloride, fluorine, interhalogens (boron trifluoride, chlorine trifluoride) and phosphorus pentoxide. May react violently with incompatible products (Ref Section 10).
Special protective equipment and precautions for firefighters	Discard incompatible substances if this can be done without risk. Firefighters should be equipped with standard protective equipment, fireproof clothing, face mask, gloves, protective boots and, where appropriate, self-contained breathing apparatus.

SECTION 06 - ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up / Personnel precautions, protective equipment	Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment. Pick up with a shovel or broom, taking care not to scatter dust. Dispose of residues in a container provided for the disposal of hazardous materials. Do not let product enter drains.
--	--

SECTION 07 - HANDLING AND STORAGE

Conditions for safe storage	Reacts violently with water. Keep container tightly closed in a dry and well-ventilated place. Store in a cool, dry place. Moisture sensitive. Hygroscopic.
Methods of handling	Keep away from moisture. Avoid contact with the skin, eyes and clothes. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust or vapor is formed.

SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Calcium oxide	1305-78-8	TWA	2.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required			
		TWA	2.000000 mg/m3	Canada. British Columbia OEL
		TWAEV	2.000000 mg/m3	Canada. Ontario OELs
		TWAEV	2.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWAEV	2 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	2 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		TWA	2.000000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)

Data source	Sigma-Aldrich.
Ventilation	Fan.
Respiratory	If the permissible levels are exceeded, use a mechanical filter / cartridge against NIOSH vapors or a respirator with air supply.
Gloves	Handle with gloves.
Eyes	Safety goggles with safety shutters.
Shoes	Use safety shoes.
Clothing	Labcoat. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Engineering control	Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Solid.
Appearance	Poudre blanche.
Odour	inodore.
Odour threshold	Data not available
pH	12.5-12.8 à 1.65 g/L à 25°C.
Melting point / Freezing point	2570°C
Initial boiling point	2850°C
Boiling range	Data not available
Flash point	Data not available
Evaporation rate	Data not available
Flammability	No
Lower flammable / Explosive limit	Data not available
Upper flammable / Explosive limit	Data not available
Vapour pressure	Data not available
Vapour density	Data not available
Relative density	3.3 g/cm ³ à 20°C.
Solubility	Soluble dans l'eau (956 - 1 337.6 mg/L @ 20 °C) soluble dans l'acide et glycérol; pratiquement insoluble dans l'alcool.
Partition coefficient water/n-octanol	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Viscosity	Data not available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	Stable under recommended storage conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Stable under normal conditions.
Conditions of instability (Including sensitivity to shock / static discharge / vibration)	Avoid moisture. Avoid exposure to air.
Incompatible material	Water Strong oxidizing agents. Acids Halogens, Fluorine, Hydrogen fluoride, Carbon dioxide (CO ₂), Alcohols.
Hazardous decomposition products	Hazardous decomposition products formed under fire conditions. - Calcium oxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

CALCIUM OXIDE

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Severe irritation that may cause eye damage. Causes eye burns.
- Skin	Severe irritation and dermatitis. May be harmful if absorbed through skin. Causes skin burns.
- Inhalation	The product is extremely destructive to the tissue of the mucous membranes and upper respiratory tract. Causes burns of the respiratory tract. May be harmful if inhaled.
Acute toxicity (Ingestion)	Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. May be harmful if swallowed.
Chronic exposure effects / symptoms	Burning sensation, chest pain, cough, dyspnoea, laryngitis, headache, dizziness, watery eyes, tiredness, nausea and vomiting. Inflammation of respiratory passages and ulceration and perforation of the nasal septum, as well as pneumonia.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 2000 mg/kg. LD50 Dermal - Data not available.
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 4h - 6.04 mg/L.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity	LC50 - Cyprinus carpio (Carp) - 1070 mg/L - 96 h - Static
Persistence and degradability	Data not available.
Bioaccumulative potential	Data not available.
Mobility in soil	Data not available.
Other adverse effects	May be harmful in the long term for aquatic organisms. Do not throw residues in the sewer.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of contents / container in accordance with local / regional / national / international regulations / or contact a specialist waste disposal company.
Contaminated Packaging	Dispose of as unused product.

SECTION 14 - TRANSPORT INFORMATION

UN Number	1910
UN Proper shipping name	OXYDE DE CALCIUM, réglementé seulement s'il est transporté par aéronef
Transport hazard class(es)	8 Corrosive substances
Packing group	III
Limited quantity index	5kg
ERAP Index	-
Special precautions	63

SECTION 15 - REGULATORY INFORMATION

WHIMS CANADA	Skin corrosion/irritation - Skin irritation category 2 Serious eye damage/eye irritation - Serious eye damage category 1 Specific target organ toxicity - Single exposure category 3
--------------	--

SECTION 16 - OTHER INFORMATION

Further information

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Last Update: 8/8/2019