



Centre Anti-Poison pour le Québec: (800) 463-5060

Tél. (Qc): (418) 660-8666 / 800-890-8666

Fax. (Qc): (418) 660-8998


SAFETY DATA SHEET

SECTION 01 - PRODUCT AND COMPANY IDENTIFICATION

Product Identifier LIQUID TREATMENT CHROME PICKLE		Product Use Laboratory use	
Chemical formula -		Product code DW-2000	Molar weight
Chemical name / Commercial name / Synonymous -			
Supplier's name Laboratoire MAT		Address-Street 610, Adanac Street	
City Québec		Province Québec	
Postal code G1C 7B7	Internet www.labmat.com	Phone number 418-660-8666 / 800-890-8666	
Emergency phone	CANUTEC: 613-996-6666	CENTRE ANTI-POISON DU QUÉBEC 800-463-5060	
Date SDS 4/19/2021	SDS Prepared by Laboratoire MAT	E-Mail labmat@labmat.com	

SECTION 02 - HAZARDS IDENTIFICATION

Classification WHIMS / GHS	Corrosive to metals-Category 1 Serious eye damage/eye irritation - Serious eye damage category 1 Respiratory or skin sensitization - Respiratory sensitizer category 1 Germ cell mutagenicity category 1A Carcinogenicity category 1B Reproductive toxicity category 1B Specific Target Organ Toxicity - Repeated exposure category 1 Acute toxicity - Oral category 4 Acute toxicity - Inhalation category 2 Respiratory or skin sensitization - Skin sensitize category 1 Skin corrosion/irritation - Skin corrosion category 1	
Signal Word	DANGER	
Hazards statements (H)	H290 May be corrosive to metals. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H330 Fatal if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H340 May cause genetic defects. H350 May cause cancer. H360 May damage fertility or the unborn child. H372 Causes damage to organs through prolonged or repeated exposure.	
Precautionary statements (P)	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P234 Keep only in original container. P260 Do not breathe dust / fume / gas / mist / vapors / spray. P261 Avoid breathing dust / fume / gas / mist / vapors / spray. P264 Wash the areas of the body that have been in contact with the product after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection. P284 Wear respiratory protection. P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/attention. P310 Immediately call a POISON CENTER or doctor/physician. P314 Get medical advice/attention if you feel unwell. P320 Specific treatment is urgent (see section 4 on this SDS on this label). P321 Specific treatment (see section 4 of the SDS and on this label). P330 Rinse mouth. P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.	

	P362 + P364 Take off contaminated clothing and wash it before reuse. P363 Wash contaminated clothing before reuse. P390 Absorb spillage to prevent material damage. P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P406 Store in a corrosion resistant container / or a container with corrosion resistant liner. P501 Dispose of contents/container in accordance with local / regional / national / international regulations or contact a specialist waste disposal company.
PICTOGRAMS	
Other dangers	NFPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Signifiant; 4=Extreme)
	Health 3 Fire 0 Reactivity 1 Special danger

SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingrédients (Dénomination chimique / synonymes)	Numéro CAS et tout identificateur unique	Concentration (%)
Acide nitrique	7697-37-2	7,5
Dichromate de sodium dihydrate	7789-12-0	10.2
Sulfate d'aluminium	16828-12-9	6.3
Bifluorure de sodium	1333-83-1	1.3
Eau	7732-18-5	Balance

SECTION 04 - FIRST AID MEASURES

Eye contact	Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes. If irritation persists, seek medical attention.
Skin contact	Wash skin with plenty of water for at least 15 minutes. Remove soiled clothing. If irritation persists, seek medical attention.
Inhalation	Move the unwell person to the fresh air. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	If the person is conscious, give water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.
Most important symptoms and effects (acute and delayed)	Main symptoms of high exposure: The product is toxic, corrosive and irritant. The corrosive effect will outweigh the toxicity for the concentrated product. Skin sensitizer. Respiratory sensitizer. To our knowledge, the chemical, physical and toxicological properties have not been fully investigated. Ref. section 11.
Immediate medical attention and special treatment, if necessary	In case of medical consultation, keep this sheet available.
General advice	Show this safety data sheet to the doctor in attendance.

SECTION 05 - FIREFIGHTING MEASURES

Flammability	No
Ignition conditions	No longer flammable at this concentration. Risk of fire or explosion if heated or milled in the presence of combustible or organic products. It is not considered flammable, but can burn at high temperatures.
Suitable extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	Do not use a heavy water stream.
Hazardous combustion products	Hazardous combustion products formed under fire conditions: - Sodium oxides, Chromium oxides Nitrogen oxides (NOx). Hydrogen fluoride. Forms aluminum oxide, sulfur dioxide and / or sulfur trioxide temperatures above 760 ° C (1400 ° F) or when dry alum is enclosed in a fire involving other fire.
Special fire and explosion hazards	When concentrated, the product reacts according to the following characteristics: Powerful oxidizer Sodium dichromate may react violently or explode on contact with sulfuric acid + ethanol + heat, sulfuric acid + organic residues, sulfuric acid + 2-propanol, sulfuric acid + trinitrotoluene, alcohols, acetic anhydride, boron + silicon, hydrazine and its hydrates. In the event of a fire, the water in the solution will evaporate, and the oxidizing base product will fuel the fire. May react violently with incompatible products (Ref Section 10).
Special protective equipment and precautions for firefighters	Discard incompatible substances if this can be done without risk. Firefighters should be equipped with standard protective equipment, fireproof clothing, face mask, gloves, protective boots and, where appropriate, self-contained breathing apparatus.

SECTION 06 - ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up / Personal precautions, protective equipment	Evacuate personnel to safe areas. Ensure a good ventilation of the premises. Avoid breathing vapors, mist or gas. Use personal protective equipment. Use a respirator as needed. Absorb residues with vermiculite or other absorbents. Do not use cellulose-based absorbent. Dilute residues with water, clean and rinse. When handling, wear appropriate safety equipment. Dispose of residues in a container provided for the disposal of hazardous materials. Do not let product enter drains.
---	---

SECTION 07 - HANDLING AND STORAGE

Conditions for safe storage	Store in cool place. Air-, heat-, and moisture-sensitive. Protect from the sun's rays. Keep container tightly closed in a dry and well-ventilated place. Keep container tightly closed and store away from heat, water, moisture, and incompatible products. Store away from incompatible products.
Methods of handling	Always open containers slowly to allow any excess pressure to vent. Bottle in the glass only. Avoid formation of dust and aerosols. Avoid inhalation of vapor or mist. Wear personal protective equipment when handling. Always ensure good ventilation. Transport according to TDG (ref Section 14) Keep away from sources of ignition - No smoking. Do not eat or drink while using.

SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace control parameters

Composants	No.-CAS	Valeur	Paramètres de contrôle	Base
Sodium dichromate dihydrate	7789-12-0			Canada. Alberta, Code de santé et de sécurité au travail (tableau 2 : VLE)
		TWA	0.050000 mg/m3	Canada. Alberta, Code de santé et de sécurité au travail (tableau 2 : VLE)
Remarques	Carcinogène confirmé chez les humains (veut dire que l'agent est carcinogène pour les humains)			
		VEMP	0.050000 mg/m3	Québec. Règlement sur la santé et la sécurité du travail, Annexe 1 Partie 1: Valeurs d'exposition admissibles des contaminants de l'air
Une substance dont la recirculation est prohibée conformément à l'article 108. Une substance dont l'exposition doit être réduite au minimum conformément à l'article 42. Sensibilisant Un effet cancérigène démontré chez l'humain				
		TWA	0.025000 mg/m3	Canada. LEP Colombie Britannique
L'IARC « 1 » s'applique aux substances catégorisées comme étant carcinogènes pour les humains, et il est utilisé lorsqu'il y a suffisamment de preuves de carcinogénicité chez les humains. L'ACGIH « A1 » s'applique aux substances qui sont des carcinogènes confirmés chez les humains basés sur le poids des données provenant des études épidémiologiques				
		C	0.100000 mg/m3	Canada. LEP Colombie Britannique
L'IARC « 1 » s'applique aux substances catégorisées comme étant carcinogènes pour les humains, et il est utilisé lorsqu'il y a suffisamment de preuves de carcinogénicité chez les humains. L'ACGIH « A1 » s'applique aux substances qui sont des carcinogènes confirmés chez les humains basés sur le poids des données provenant des études épidémiologiques				
				Canada. Alberta, Code de santé et de sécurité au travail (tableau 2 : VLE)
		TWA	0.05 mg/m3	Canada. Alberta, Code de santé et de sécurité au travail (tableau 2 : VLE)
Carcinogène confirmé chez les humains (veut dire que l'agent est carcinogène pour les humains)				
		VEMP	0.05 mg/m3	Québec. Règlement sur la santé et la sécurité du travail, Annexe 1 Partie 1: Valeurs d'exposition admissibles des contaminants de l'air
Une substance dont la recirculation est prohibée conformément à l'article 108. Une substance dont l'exposition doit être réduite au minimum conformément à l'article 42. Sensibilisant Un effet cancérigène démontré chez l'humain				
		TWA		
			0.025 mg/m3	Canada. LEP Colombie Britannique
L'IARC « 1 » s'applique aux substances catégorisées comme étant carcinogènes pour les humains, et il est utilisé lorsqu'il y a suffisamment de preuves de carcinogénicité chez les humains. L'ACGIH « A1 » s'applique aux substances qui sont des carcinogènes confirmés chez les humains basés sur le poids des données provenant des études épidémiologiques				
		C	0.1 mg/m3	Canada. LEP Colombie Britannique
L'IARC « 1 » s'applique aux substances catégorisées comme étant carcinogènes pour les humains, et il est utilisé lorsqu'il y a suffisamment de preuves de carcinogénicité chez les humains. L'ACGIH « A1 » s'applique aux substances qui sont des carcinogènes confirmés chez les humains basés sur le poids des données provenant des études épidémiologiques				
Composants	No.-CAS	Valeur	Paramètres de contrôle	Base
Nitric acid	7697-37-2	TWA	2.000000 ppm 5.200000 mg/m3	Canada. Alberta, Code de santé et de sécurité au travail (tableau 2 : VLE)
		STEL	4.000000 ppm 10.000000 mg/m3	Canada. Alberta, Code de santé et de sécurité au travail (tableau 2 : VLE)
		TWA	2.000000 ppm	Canada. LEP Colombie Britannique
		STEL	4.000000 ppm	Canada. LEP Colombie Britannique
		VEMP	2.000000 ppm 5.200000 mg/m3	Québec. Règlement sur la santé et la sécurité du travail, Annexe 1 Partie 1: Valeurs d'exposition admissibles des contaminants de l'air
		VECD	4.000000 ppm	Québec. Règlement sur la santé et la sécurité du travail, Annexe 1 Partie 1: Valeurs

			10.000000 mg/m3	d'exposition admissibles des contaminants de l'air
Composants	No.-CAS	Paramètres de contrôle	Valeur	Base
Sodium bifluoride	1333-83-1	VECD, VEMP, DIVS	Donnée non disponible	Canada. Alberta, Code de santé et de sécurité au travail (tableau 2 : VLE)
		VECD, VEMP, DIVS	Donnée non disponible	Canada. LEP Colombie Britannique
		VECD, VEMP, DIVS	Donnée non disponible	Québec. Règlement sur la santé et la sécurité du travail, Annexe 1 Partie 1: Valeurs d'exposition admissibles des contaminants de l'air

Composants	No.-CAS	Valeur	Paramètres de contrôle	Base
Aluminium sulphate hydrates	16828-12-9	VECD, VEMP, DIVS	Donnée non disponible	Canada. Alberta, Code de santé et de sécurité au travail (tableau 2 : VLE)
		VECD, VEMP, DIVS	Donnée non disponible	Canada. LEP Colombie Britannique
		VECD, VEMP, DIVS	Donnée non disponible	Québec. Règlement sur la santé et la sécurité du travail, Annexe 1 Partie 1: Valeurs d'exposition admissibles des contaminants de l'air

Data source	Sigma-Aldrich.
Ventilation	Fan.
Respiratory	If the permissible levels are exceeded, use a mechanical filter / cartridge against NIOSH vapors or a respirator with air supply.
Gloves	Handle with gloves.
Eyes	Safety goggles with safety shutters.
Shoes	Safety shoes.
Clothing	Labcoat.
Engineering control	Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid.
Appearance	Liquide de couleur orangé vif-
Odour	Légère odeur acide.
Odour threshold	Data not available
pH	2.
Melting point / Freezing point	Data not available
Initial boiling point	Data not available
Boiling range	Data not available
Flash point	Data not available
Evaporation rate	Data not available
Flammability	No
Lower flammable / Explosive limit	Data not available
Upper flammable / Explosive limit	Data not available
Vapour pressure	Data not available
Solubility	Soluble dans l'eau..
Vapour density	Data not available
Relative density	Data not available
Partition coefficient water/n-octanol	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Viscosity	Data not available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	Acid product, reacts strongly with strong bases. May react violently with incompatible substances.
Chemical stability	Stable under recommended storage conditions. Sensitive to heat. Sensitive to light.
Possibility of hazardous reactions	Oxidizer. Stable under normal conditions.
Conditions of instability (Including sensitivity to shock / static discharge / vibration)	Avoid contact with incompatible materials. Avoid moisture and excessive heat. Sun exposure. Exposure to the air. Nitric acid is yellowish in color when exposed to light. Old inventories of nitric acid (10 years and over) or yellowish-colored batches formed a nitroze compound with a very explosive potential. Old nitric acid inventories (10 years and older) or yellowish-colored batches have formed a nitroz compound with very explosive potential.
Incompatible material	When pure, the products react with the following products: Organic materials, acids, water, strong bases, acid anhydrides, metals, reducing agents, metallic powders, strong reducing agents, combustible material. Alcohols. Nitric acid is incompatible with bases, most metals, especially alkali metals, powdered metals, metal oxides, reducing agents, organic substances, including anhydrides, alcohols, aldehydes, ketones, ethers, amines, hydrocarbons, toluene, acetonitrile, acrylonitrile, chlorobenzene, methylene chloride, etc., combustible organic materials such as paper, charcoal, wood dust, etc. and with many sulphides, nonmetallic hydrides, carbides, and acetylenides. Strong oxidizing agents (nitric acid, perchloric acid, peroxides, chlorates and perchlorates). Strong bases. Sodium, Sodium Oxides, Potassium. Aluminum and Zinc (specially in the presence of water or moisture). Sodium bifluoride is incompatible with sulfuric acid, caustics, ammonia, amines, organic anhydrides, isocyanates, vinyl acetate, alkylene oxides and epichlorohydrin. he corrodes glass, concrete and metals containing silica. The dissolution of sodium bifluoride in the water gives off heat.
Hazardous decomposition products	Hazardous decomposition products formed under fire conditions. - Sodium oxides, Chromium oxides Hydrogen fluoride, Sodium oxides. - Sulphur oxides, Aluminum oxide Nitrogen oxides.

SECTION 11 - TOXICOLOGICAL INFORMATION

SODIUM DICHROMATE DIHYDRATE

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Severe irritation and may result in inflammation of the conjunctiva.
- Skin	Irritation and dermatitis. Exposed areas of the skin, including the fingers, the back of the hand and the forearms may present small ulcerations ("chrome sori").
- Inhalation	Irritation of the mucous membranes and respiratory tract. Nervous disorders, chest pain, cough, dyspnea, pharyngitis, headache, dizziness, fever, sweating, salivation, nausea and vomiting.
Acute toxicity (Ingestion)	Severe irritation of the digestive tract. Dysphagia, abdominal pain, haemorrhagic enteritis, cramps, diarrhea, melena, intense thirst, nausea and vomiting, tubular nephritis and possible hepatotoxicity, convulsions, circulatory collapse, unconsciousness, coma and can lead to death.
Chronic exposure effects / symptoms	Burning sensation, dermatitis, conjunctivitis, skin reactions (chromium sori), liver and kidney damage, chest pain, cough, dyspnoea, laryngitis, pharyngitis, headache, dizziness, ulceration and perforation of the nasal septum, discoloration teeth, metallic taste in the mouth, fatigue, digestive disorders (inflammation and ulceration of the gastrointestinal tract), weight loss and loss of appetite, convulsions, nausea and vomiting. Prolonged exposure to this product is likely to cause cancer.
DL50 (specify species and route of entry)	Data based on the anhydrous product: LD50 Oral - Rat - 67 mg/kg. LD50 Dermal - Rabbit - 2000 mg/kg.
CL50 (specify species and route of entry)	Data based on the anhydrous product: LC50 Inhalation - Rat - 4h - 83 - 99 mg/m ³ .

ALUMINUM SULFATE (HYDRATE)

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Causes serious eye irritation.
- Skin	Causes skin irritation.
- Inhalation	Irritation of the mucous membranes and respiratory tract. Nervous disorders, dizziness, cough, dyspnea, headache, nausea and vomiting.
Acute toxicity (Ingestion)	Irritation of the mucous membranes. Nervous disorders, gastrointestinal disorders, cramps, diarrhea, headache, convulsions, nausea and vomiting.
Chronic exposure effects / symptoms	Sensation de brûlure, troubles nerveux, vertiges, maux de tête, toux, dyspnée, laryngite, perte d'appétit, nausées et vomissements.
DL50 (specify species and route of entry)	DL50 Oral - Mouse - 6207 mg/Kg LD50 Dermal - Data not available.
CL50 (specify species and route of entry)	LC50 - Inhalation - Data not available.

NITRIC ACID

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Irritation and tearing. Severe burns and destruction of ocular tissue that can lead to corneal ulceration and blindness.
- Skin	May be harmful if absorbed through skin. Severe burns and tissue ulcerations.
- Inhalation	Spasms, irritation and inflammation of the nose, throat and lungs. Cough, dyspnea, cyanosis, chest pain. Edema of the larynx and bronchi. Chemical pneumonitis and pulmonary edema that can lead to death.
Acute toxicity (Ingestion)	Corrosion and ulceration of the mouth, throat, esophagus, stomach and abdominal wall.
Chronic exposure effects / symptoms	Dental erosions have been attributed to repeated exposures. To our knowledge, the chemical, physical and toxicological properties have not been fully investigated.
DL50 (specify species and route of entry)	LD50 Oral - Data not available. LD50 Dermal - Data not available.
CL50 (specify species and route of entry)	Inhalation: 67 ppm, 4hres, Mouse

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Causes eye burns.
- Skin	May be harmful if absorbed through skin. Causes skin burns.
- Inhalation	May be harmful if inhaled. The product is extremely destructive to the tissue of the mucous membranes and upper respiratory tract.
Acute toxicity (Ingestion)	Toxic if swallowed.
Chronic exposure effects / symptoms	The product is extremely destructive of the tissues of the mucous membranes, upper respiratory tract, eyes and skin, spasm, inflammation and edema of the larynx, spasm, inflammation and bronchial edema, congestion Pulmonary edema, burning sensation, cough, asthma, laryngitis, respiratory failure, migraine, Nausea. Severe irritation (possible burn): eyes, skin, respiratory tract (if inhaled); salivation, nausea, abdominal pain, vomiting, diarrhea; muscle pain, paresthesia, hyper-reflexivity, convulsions; shock, death from heart failure or respiratory paralysis.
DL50 (specify species and route of entry)	LD50 Oral - Data not available; LD50 Dermal - Data not available.
CL50 (specify species and route of entry)	LC50 - Inhalation - Data not available.

SUMMARY

Acute exposure effects / Symptoms:	By exposure routes below.
Ingestion	To our knowledge, the product has not been fully evaluated
Inhalation	To our knowledge, the product has not been fully evaluated
Skin	To our knowledge, the product has not been fully evaluated
Eyes	To our knowledge, the product has not been fully evaluated
Chronic exposure effects / Symptoms:	To our knowledge, the product has not been fully evaluated
ETA Mix (Estimated Acute Toxicity)	LD50 Oral: 599 mg/kg - Rat LD50 Dermal: > 5000 mg/kg - Undefined species LC50 Inhalation: 0.8 mg/L - 4h - Rat

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity	Data not available.
Persistence and degradability	Data not available.
Bioaccumulative potential	Data not available.
Mobility in soil	Data not available.
Other adverse effects	Very toxic to aquatic life with long lasting effects. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of contents / container in accordance with local / regional / national / international regulations / or contact a specialist waste disposal company.
Contaminated Packaging	Dispose of as unused product.

SECTION 14 - TRANSPORT INFORMATION

UN Number	2922
UN Proper shipping name	LIQUIDE CORROSIF, TOXIQUE, N.S.A.
Transport hazard class(es)	8 Corrosive substances 6.1 Toxic substances
Packing group	II
Limited quantity index	1L
ERAP Index	-
Special precautions	16 .(dichromate de sodium,HNO3, Na2F)

SECTION 15 - REGULATORY INFORMATION

WHIMS CANADA	Corrosive to metals-Category 1 Serious eye damage/eye irritation - Serious eye damage category 1 Respiratory or skin sensitization - Respiratory sensitizer category 1 Germ cell mutagenicity category 1A Carcinogenicity category 1B Reproductive toxicity category 1B Specific Target Organ Toxicity - Repeated exposure category 1 Acute toxicity - Oral category 4 Acute toxicity - Inhalation category 2 Respiratory or skin sensitization - Skin sensitize category 1 Skin corrosion/irritation - Skin corrosion category 1
--------------	---

SECTION 16 - OTHER INFORMATION

Further information

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Last Update: 4/19/2021