



Centre Anti-Poison pour le Québec: (800) 463-5060

Tél. (Qc): (418) 660-8666 / 800-890-8666

Fax. (Qc): (418) 660-8998


SAFETY DATA SHEET

SECTION 01 - PRODUCT AND COMPANY IDENTIFICATION

Product Identifier EMBALMING SOLUTION		Product Use Laboratory use	
Chemical formula -		Product code ES-2799	Molar weight
Chemical name / Commercial name / Synonymous Solution d'embaumement-solution d'injection			
Supplier's name Laboratoire MAT		Address-Street 610, Adanac Street	
City Québec		Province Québec	
Postal code G1C 7B7	Internet www.labmat.com	Phone number 418-660-8666 / 800-890-8666	
Emergency phone	CANUTEC: 613-996-6666 CENTRE ANTI-POISON DU QUÉBEC 800-463-5060		
Date SDS 12/6/2022	SDS Prepared by Laboratoire MAT	E-Mail labmat@labmat.com	

SECTION 02 - HAZARDS IDENTIFICATION

Classification WHIMS / GHS	Serious eye damage/eye irritation - Serious eye damage category 1 Germ cell mutagenicity category 2 Flammable liquids category 2 Carcinogenicity category 1A Specific Target Organ Toxicity - Single exposure category 1 Specific Target Organ Toxicity - Repeated exposure category 1 Respiratory or skin sensitization - Skin sensitize category 1 Skin corrosion/irritation - Skin corrosion category 1	
Signal Word	DANGER	
Hazards statements (H)	H318 Causes serious eye damage. H341 Suspected of causing genetic defects . H225 Highly flammable liquid and vapor. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H350 May cause cancer. H370 Causes damage to organs. H372 Causes damage to organs through prolonged or repeated exposure.	
Precautionary statements (P)	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P280 Wear protective gloves/protective clothing/eye protection/face protection. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/attention. P310 Immediately call a POISON CENTER or doctor/physician. P405 Store locked up. P501 Dispose of contents/container in accordance with local / regional / national / international regulations or contact a specialist waste disposal company. P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe dust / fume / gas / mist / vapors / spray. P261 Avoid breathing dust / fume / gas / mist / vapors / spray. P264 Wash the areas of the body that have been in contact with the product after handling. P270 Do no eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P308 + P311 IF exposed or concerned: Call a POISON CENTER or a doctor. P314 Get medical advice/attention if you feel unwell. P321 Specific treatment (see section 4 of the SDS and on this label). P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P363 Wash contaminated clothing before reuse. P370 + P378 In case of fire: Use water spray or alcohol-resistant foam, or dry powder or carbon dioxide for extinction. P403 + P235 Store in a well-ventilated place. Keep cool.	

PICTOGRAMS	
Other dangers	NFPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Significant; 4=Extreme)
	Health 3 Fire 2 Reactivity 0 Special danger

SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingrédients (Dénomination chimique / synonymes)	Numéro CAS et tout identificateur unique	Concentration (%)
Éthanol	64-17-5	8.8
Phénol	108-95-2	5.7
Glycérine	56-81-5	77
Formaldéhyde	50-00-0	2.3
Méthanol	67-56-1	2.3
Acétate d'éthyle	141-78-6	0.1
Eau	7732-18-5	3.7

SECTION 04 - FIRST AID MEASURES

Eye contact	Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes. If irritation persists, seek medical attention.
Skin contact	Wash skin with plenty of water for at least 15 minutes. Remove soiled clothing. If irritation persists, seek medical attention.
Inhalation	If breathed in, move person into fresh air. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	If the person is conscious, give water to drink. Never give anything by mouth to an unconscious person. Consult a physician.
Most important symptoms and effects (acute and delayed)	Main symptoms of high exposure: Skin, eye and respiratory system irritation. Headaches. Blurry vision. Vomiting. Nausea. Tiredness. Diarrhea. Abdominal pain. Convulsions. To our knowledge, the chemical, physical and toxicological properties have not been fully investigated. Ref. section 11.
Immediate medical attention and special treatment, if necessary	In case of medical consultation, keep this sheet available.
General advice	Show this safety data sheet to the doctor in attendance.

SECTION 06 - ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up / Personnel precautions, protective equipment	Evacuate personnel to safe areas. Cut off all sources of ignition. Absorb the product with sand or vermiculite. Dilute residues with water, clean and rinse. Ensure a good ventilation of the premises. Dispose of residues in a container for disposal of hazardous materials. When handling, wear suitable safety equipment. Use breathing apparatus if necessary. Avoid breathing vapors, mist or gas. Do not let product enter drains.
--	--

SECTION 07 - HANDLING AND STORAGE

Conditions for safe storage	Store in a cool, dry place. Store in a well-ventilated area. Keep container tightly closed and store away from incompatible products, heat, sparks, and open flame. Keep away from sources of ignition - No smoking. Take measures to prevent the accumulation of electrostatic charges. Protect from sunlight and light.
Methods of handling	Always open containers slowly to allow any excess pressure to vent. Avoid formation of dust and aerosols. Ensure good ventilation. Avoid ingestion and inhalation. Wear personal protective equipment when handling. Always ensure good ventilation. Transport according to TDG (ref Section 14)

SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace control parameters

Components	CAS-No.	Control parameters	Value	Basis
Ethanol	64-17-5	TWAEV	1000 ppm 1900 mg/m ³	Canada. Ontario OELs
		TWA	1000 ppm 1880mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		VEMP	1000 ppm 1880mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEL	1000 ppm	Canada. British Columbia OEL
		TWA	1000 ppm	Canada. British Columbia OEL

Components	CAS-No.	Control parameters	Value	Basis
Ethyl acetate	141-78-6	TWA	400.000000 ppm 1,440.000000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required			
		TWA	150.000000 ppm	Canada. British Columbia OEL
		TWAEV	400.000000 ppm 1,440.000000 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	400.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)

Components	CAS-No.	Control parameters	Value	Basis
Methanol	67-56-1	TWA	200.000000 ppm 262.000000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Substance may be readily absorbed through intact skin			
		STEL	250.000000 ppm 328.000000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
	Substance may be readily absorbed through intact skin			
		TWA	200.000000 ppm	Canada. British Columbia OEL

Contributes significantly to the overall exposure by the skin route.				
		STEL	250.000000 ppm	Canada. British Columbia OEL
Contributes significantly to the overall exposure by the skin route.				
		TWAEV	200.000000 ppm 262.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
Skin (percutaneous)				
		STEV	250.000000 ppm 328.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
Skin (percutaneous)				
		TWA	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	250.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)

Components	CAS-No.	Control parameters	Value	Basis
Phenol	108-95-2	TWA	5.000000 ppm 19.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Substance may be readily absorbed through intact skin			
		TWA	5.000000 ppm	Canada. British Columbia OEL
Contributes significantly to the overall exposure by the skin route.				
		TWAEV	5.000000 ppm 19.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
Skin (percutaneous)				
		TWA	5.000000 ppm	USA. ACGIH Threshold Limit Values

Component	No.-CAS	Control parameters	Value	(TLV) Base
Formaldéhyde	50-00-0	(c)	1.000000 ppm 1.300000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarques	carcinogen class A1			
		TWA	0.750000 ppm 0.900000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
	carcinogen class A1			
		TWA	0.300000 ppm	Canada. British Columbia OEL
	carcinogen class A1			
		C	1.000000 ppm	Canada. British Columbia OEL
	carcinogen class A1			
		P	2.000000 ppm 3.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	carcinogen class A1			

Components	CAS-No.	Control parameters	Value	Basis
Glycerol	56-81-5	TWA	10.000000 mg/m3	Canada. British Columbia OEL
		TWA	3.000000 mg/m3	Canada. British Columbia OEL
		TWA	10.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required			
		TWAEV	10.000000 mg/m3	Canada. Ontario OELs
		TWAEV	10 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1:

				Permissible exposure values for airborne contaminants
		TWAEV	10.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	10.000000 mg/m3	Canada. British Columbia OEL
		TWA	3.000000 mg/m3	Canada. British Columbia OEL
		TWA	10.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required				
		TWAEV	10.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	10.000000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)

Data source	Sigma-Aldrich (Millipore Sigma)
Ventilation	Use fan.
Respiratory	If work under the hood is not possible, or if the permissible levels are exceeded, use a mechanical filter / cartridge against NIOSH vapors or a respirator with air supply.
Gloves	Handle with gloves.
Eyes	Safety goggles with safety shutters. Face shield (20 cm minimum).
Shoes	Safety shoes.
Clothing	Labcoat. Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Engineering control	Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid.
Appearance	Liquide visqueux incolore.
Odour	Odeur de phénol.
Odour threshold	Data not available
pH	Donnée non disponible.
Melting point / Freezing point	Data not available
Initial boiling point	Data not available
Boiling range	Data not available
Flash point	Data not available
Evaporation rate	Data not available
Flammability	Yes
Lower flammable / Explosive limit	Data not available
Upper flammable / Explosive limit	Data not available
Vapour pressure	Data not available
Solubility	Soluble dans l'eau, dans l'alcool, le chloroforme, l'éther et la glycérine.
Vapour density	Data not available
Relative density	1.164 g/ml (Théorique).
Partition coefficient water/n-octanol	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Viscosity	Data not available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	May react violently with incompatible substances. May ignite on contact with oxidants.
Chemical stability	If heated strongly, it emits toxic fumes.
Possibility of hazardous reactions	May react violently with incompatible substances.
Conditions of instability (Including sensitivity to shock / static discharge / vibration)	This product may turn pink if exposed to air or light.
Incompatible material	When pure, the products react with the following products: Acids, Oxidants, Acid Chlorides, Acid Anhydrides, Alkali Metals, Reducing Agents. Strong oxidizing agents (nitric acid, perchloric acid, peroxides, chlorates and perchlorates), strong acids and bases, strong oxidants, alkalis, acetaldehyde, 1,3-butadiene, boron trifluoride, camphor, diethyletherate, calcium hypochlorite, formaldehyde, metals and their alloys, sodium nitrite, heat, air, moisture and light. Glycerine can react with strong oxidizing agents (nitric acid, perchloric acid, peroxides, chlorates and perchlorates), strong bases, acetic anhydride, chromic anhydride, calcium hypochlorite, chlorine chromium oxide, phosphorus triiodide, potassium permanganate, sodium hydride.
Hazardous decomposition products	Hazardous decomposition products formed under fire conditions. Toxic vapors of carbon monoxide and dioxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

LIQUIFIED PHENOL

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Irritation and severe burns that can lead to corneal ulceration and blindness.
- Skin	Severe irritation, burns and tissue ulcerations.
- Inhalation	Spasms, irritation and inflammation of the nose, throat and lungs. Edema of the larynx and bronchi. Chemical pneumonitis and pulmonary edema that can lead to death.
Acute toxicity (Ingestion)	Irritation and burning of the mouth, throat, esophagus and abdominal wall. Dysphagia, abdominal pain, cramps, diarrhea, melena, hematemesis, sweating, salivation, paleness, convulsions, cardiac arrhythmia, stupor, hypotension, unconsciousness, coma and can lead to death. Ingestion of 1.5 g is sufficient to cause death.
Chronic exposure effects / symptoms	Burning sensation, dermatitis, vitiligo, nervous disorders, liver and kidney damage, chest pain, cough, dyspnoea, laryngitis, headache, diarrhea, dizziness, confusion, irritability, erythema, difficulty swallowing, sweating, salivation muscle weakness and pain, weight loss and loss of appetite, nausea and vomiting.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 340-650 mg/kg LD50 Dermal - Rabbit - 850-1400 mg/kg LD50 Dermal - Rat - 660 mg/kg
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 4h - 316 mg/m3.

FORMALDEHYDE 37%

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Severe irritation and burns that may cause permanent eye damage.
- Skin	Irritation and dermatitis. Prolonged skin contact may result in an allergic reaction characterized mainly by erythematous or eczematous lesions.
- Inhalation	Irritation of the mucous membranes and respiratory tract. Pains in the chest, respiratory allergies, cough, dyspnea, headache, dizziness, watery eyes, congestion, bronchial spasms and may lead to pulmonary edema.
Acute toxicity (Ingestion)	Irritation and burning of the esophagus and stomach. Abdominal pain, cramps, diarrhea, nausea and vomiting, hematemesis, acidosis, hematuria, anuria, vertigo, pallor, blindness, convulsions, stupor, respiratory collapse, coma and can lead to death.
Chronic exposure effects / symptoms	Is recognized as a carcinogen (class 1) by IARC. Burning sensation, dermatitis, conjunctivitis, chest pain, eye and lung damage, respiratory and skin allergies, cough, dyspnoea, bronchitis, dry throat, headache, dizziness, confusion, irritability, tearing, choking, sleep, intense thirst, sweating, salivation, fatigue, paleness, muscle weakness, weight loss and loss of appetite, convulsions, nausea and vomiting.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 460 mg/kg. LD50 Dermal - Data not available.
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 4h - 463 ppm.

ETHANOL (ABSOLU)

Routes of exposure	Ingestion.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Irritation and tearing.
- Skin	May cause skin irritation.
- Inhalation	May cause respiratory tract irritation.
Acute toxicity (Ingestion)	Euphoria, a feeling of intoxication, followed by central nervous system depression, which may include headache, nausea, dizziness, incoordination, speech disturbance, mental confusion and of narcosis.
Chronic exposure effects / symptoms	Cirrhosis of the liver and various diseases affecting the gastrointestinal, cardiovascular, nervous, hematological and respiratory systems.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 7000 mg/kg LD50 Dermal - Rabbit - > 2,000 mg / kg
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 4h - 116 mg/L. LC50 Inhalation - Mouse - 1h - 60000 ppm.

METHANOL

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	May cause eye irritation.
- Skin	Irritation and dermatitis.
- Inhalation	Irritation of the mucous membranes and respiratory tract. Narcotic effects, chest pain, cough, dyspnea, headache, dizziness, watery eyes, paresthesia, nystagmus, drowsiness, confusion, nausea and vomiting.
Acute toxicity (Ingestion)	Irritation of the mucous membranes. Narcotic effects, liver, kidney and eye damage, abdominal pain, cramps, diarrhea, headache, dizziness, paresthesia, nystagmus, drowsiness, incoordination, acidosis, nausea and vomiting, seizures, hypotension, respiratory collapse, loss of consciousness, coma and can lead to death. Acute absorption of methanol can cause blindness. Damage to: liver, kidneys, eyes, heart, central nervous system.
Chronic exposure effects / symptoms	Headache, dizziness, nausea, visual disturbances, decreased visual acuity, liver and kidney damage.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 1187 mg/kg LD50 Dermal - Lapin-15840 mg/kg
CL50 (specify species and route of entry)	LC50 Inhalation - Rat: 64000 ppm/4 h. LC50 Inhalation - Rat 115.9-130.7mg/L air / 4h.

ETHYL ACETATE

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Irritation and conjunctivitis. May cause opacification of the cornea.
- Skin	Irritation and dermatitis.
- Inhalation	Irritation of the mucous membranes and respiratory tract. Narcotic effects, cough, dyspnea, headache, dizziness, drowsiness, paresthesia, nystagmus, nausea and vomiting, convulsions and may result in unconsciousness.
Acute toxicity (Ingestion)	Irritation of the mucous membranes. Narcotic effects, liver and kidney damage, gastrointestinal disorders, cramps, diarrhea, headache, dizziness, drowsiness, tremors, convulsions, nausea and vomiting.
Chronic exposure effects / symptoms	Chronic poisoning can result in anemia and the appearance of leukocytosis. Burning sensation, dermatitis, conjunctivitis, narcotic effects, liver and kidney damage, chest pain, cough, dyspnea, laryngitis, headache, dizziness, somnolence, paresthesia, nystagmus, muscle weakness, weight loss, and loss of weight. appetite, nausea and vomiting.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 4934 mg/kg. LD50 Dermal - Rabbit - >5000mg/kg
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 4h - 4000 ppm. LC50 Inhalation - Mouse - 4h - 1500 ppm

GLYCERIN (GLYCEROL)

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	May cause eye irritation. May cause inflammation of the conjunctiva.
- Skin	May cause skin irritation.
- Inhalation	Irritation of the mucous membranes and respiratory tract.
Acute toxicity (Ingestion)	Irritation of the mucous membranes. Gastrointestinal disorders, cramps, diarrhea, headache, dizziness, convulsions, nausea and vomiting.
Chronic exposure effects / symptoms	Burning sensation, conjunctivitis, nervous disorders, headache, dizziness, tiredness, nausea and vomiting.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 12,600 mg/kg. LD50 Dermal - Rabbit - >10 000 mg/kg
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 1h - > 570 mg/cu m

SUMMARY

Acute exposure effects / Symptoms:	By exposure routes below.
Ingestion	To our knowledge, the product has not been fully evaluated
Inhalation	To our knowledge, the product has not been fully evaluated
Skin	To our knowledge, the product has not been fully evaluated
Eyes	To our knowledge, the product has not been fully evaluated
Chronic exposure effects / Symptoms:	To our knowledge, the product has not been fully evaluated
ETA Mix (Estimated Acute Toxicity)	LD50 Oral: 3219 mg/kg - Rat LD50 Dermal: 6882 mg/kg - Rabbit LC50 Inhalation: 182 mg/m3 - 4h - Undefined species

SECTION 12 - ECOLOGICAL INFORMATION

Available ecological information	No
----------------------------------	----

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of contents / container in accordance with local / regional / national / international regulations / or contact a specialist waste disposal company.
Contaminated Packaging	Dispose of as unused product.

SECTION 14 - TRANSPORT INFORMATION

UN Number	1992
UN Proper shipping name	LIQUIDE INFLAMMABLE, N.S.A. (Éthanol, méthanol)
Transport hazard class(es)	3 Flammable liquids
Packing group	II
Limited quantity index	1L
ERAP Index	-
Special precautions	16,150

SECTION 15 - REGULATORY INFORMATION

WHIMS CANADA	Serious eye damage/eye irritation - Serious eye damage category 1 Germ cell mutagenicity category 2 Flammable liquids category 2 Carcinogenicity category 1A Specific Target Organ Toxicity - Single exposure category 1 Specific Target Organ Toxicity - Repeated exposure category 1 Respiratory or skin sensitization - Skin sensitize category 1 Skin corrosion/irritation - Skin corrosion category 1
--------------	---

SECTION 16 - OTHER INFORMATION

Further information

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Last Update: 12/6/2022