



Centre Anti-Poison pour le Québec: (800) 463-5060

Tél. (Qc): (418) 660-8666 / 800-890-8666


Fax. (Qc): (418) 660-8998

SAFETY DATA SHEET

SECTION 01 - PRODUCT AND COMPANY IDENTIFICATION

Product Identifier FERROUS SULFATE 100g/L IN SULFURIC ACID 1N		Product Use Laboratory use	
Chemical formula -		Product code FS-1544	Molar weight
Chemical name / Commercial name / Synonymous -			
Supplier's name Laboratoire MAT		Address-Street 610, Adanac Street	
City Québec		Province Québec	
Postal code G1C 7B7	Internet www.labmat.com	Phone number 418-660-8666 / 800-890-8666	
Emergency phone	CANUTEC: 613-996-6666	CENTRE ANTI-POISON DU QUÉBEC 800-463-5060	
Date SDS 2/3/2020	SDS Prepared by Laboratoire MAT	E-Mail labmat@labmat.com	

SECTION 02 - HAZARDS IDENTIFICATION

Classification WHIMS / GHS	Corrosive to metals-Category 1 Serious eye damage/eye irritation - Serious eye damage category 1 Skin corrosion/irritation - Skin corrosion category 1	
Signal Word	DANGER	
Hazards statements (H)	H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage.	
Precautionary statements (P)	P234 Keep only in original container. P260 Do not breathe dust / fume / gas / mist / vapours / spray. P264 Wash the areas of the body that have been in contact with the product after handling. P280 Wear protective gloves/protective clothing/eye protection/face protection. P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER or doctor/physician. P321 Specific treatment (see section 4 of the SDS and on this label). P363 Wash contaminated clothing before reuse. P390 Absorb spillage to prevent material damage. P405 Store locked up. P406 Store in a corrosion resistant container / or a container with corrosion resistant liner. P501 Dispose of contents/container in accordance with local / regional / national / international regulations or contact a specialist waste disposal company.	
PICTOGRAMS		
Other dangers	NFPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Signifiant; 4=Extreme)	
	Health 2 Fire 0 Reactivity 0 Special danger	

SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingrédients (Dénomination chimique / synonymes)	Numéro CAS et tout identificateur unique	Concentration (%)
Acide sulfurique	7664-93-9	5
Sulfate ferreux heptahydrate	7782-63-0	9
Eau	7732-18-5	Balance

SECTION 04 - FIRST AID MEASURES

Eye contact	Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes. If irritation persists, seek medical attention.
Skin contact	Wash skin with plenty of water for at least 15 minutes. Remove soiled clothing. If irritation persists, seek medical attention.
Inhalation	Move the unwell person to the fresh air. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	If the person is conscious, give water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.
Most important symptoms and effects (acute and delayed)	Ref. section 11.
Immediate medical attention and special treatment, if necessary	In case of medical consultation, keep this sheet available.
General advice	Show this safety data sheet to the doctor in attendance.

SECTION 05 - FIREFIGHTING MEASURES

Flammability	No
Ignition conditions	Not flammable or combustible.
Suitable extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	Do not use a heavy water stream.
Hazardous combustion / decomposition products	Hazardous decomposition products formed under fire conditions. - Sulphur oxides - Iron oxides.
Special fire and explosion hazards	When concentrated, the product reacts according to the following characteristics: Risk of fire or explosion if heated in the presence of combustible products. May react violently with incompatible products (Ref Section 10).
Special protective equipment and precautions for firefighters	Discard incompatible substances if this can be done without risk. Firefighters should be equipped with standard protective equipment, fireproof clothing, face mask, gloves, protective boots and, where appropriate, self-contained breathing apparatus.

SECTION 06 - ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up / Personnel precautions, protective equipment	Evacuate personnel to safe areas. Absorb residues with vermiculite or other absorbents. Dispose of residues in a container provided for the disposal of hazardous materials. Ensure a good ventilation of the premises. Dilute residues with water, clean and rinse. When handling, wear appropriate safety equipment.
--	--

SECTION 07 - HANDLING AND STORAGE

Conditions for safe storage	Store in cool place. Keep container tightly closed and store away from heat, water, moisture, and incompatible products. Protect from the sun's rays. Keep container tightly closed in a dry and well-ventilated place.
Methods of handling	Wear personal protective equipment when handling. Always ensure good ventilation. Transport according to TDG (ref Section 14)

SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Sulfuric acid	7664-93-9	TWA	0.2 mg/m ³	Canada. British Columbia OEL
Remarks	ACGIH 'A2' applies to those substances that are considered suspected human carcinogens. IARC '1' applies to substances categorized as carcinogenic to humans, and used when there is sufficient evidence of carcinogenicity in humans.			
		TWAEV	0.2 mg/m ³	Canada. Ontario OELs
		STEV	3 mg/m ³	Canada. Ontario OELs
		STEL	3 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	1 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	1 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEL	3 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	0.2 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
Components	CAS-No.	Value	Control parameters	Basis
Ferrous sulfate heptahydrate	7782-63-0	TWA	1.000000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required			
		TWAEV	1.000000 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWAEV	1.000000 mg/m ³	Canada. Ontario OELs
		TWA	1.000000 mg/m ³	Canada. British Columbia OEL
		STEL	2.000000 mg/m ³	Canada. British Columbia OEL
		TWA	1 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required			
		TWAEV	1 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	1 mg/m ³	Canada. British Columbia OEL
		STEL	2 mg/m ³	Canada. British Columbia OEL
		TWA	1.000000 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
		TWA	1 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)

Data source	Sigma-Aldrich (Millipore Sigma)
Ventilation	Fan.
Respiratory	If the permissible levels are exceeded, use a mechanical filter / cartridge against NIOSH vapors or a respirator with air supply.
Gloves	Handle with gloves.
Eyes	Safety goggles with safety shutters.
Shoes	Safety shoes.
Clothing	Labcoat. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Engineering control	Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid.
Appearance	Vert pâle translucide-
Odour	Irritante.
Odour threshold	Data not available
pH	<1.
Melting point / Freezing point	Data not available
Initial boiling point	Data not available
Boiling range	Data not available
Flash point	Data not available
Evaporation rate	Data not available
Flammability	No
Lower flammable / Explosive limit	Data not available
Upper flammable / Explosive limit	Data not available
Vapour pressure	Data not available
Solubility	Miscible avec l'eau en toutes proportions. Miscible partiellement avec l'alcool.
Vapour density	Data not available
Relative density	1.08g/ml
Partition coefficient water/n-octanol	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Viscosity	Data not available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	Non-reactive under normal conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Stable under normal conditions.
Conditions of instability (Including sensitivity to shock / static discharge / vibration)	Avoid contact with incompatible materials and extreme temperatures.
Incompatible material	Water, metals, alcohols, reducing agents, bases, organic and combustible materials, azides, bromates, carbides, chlorates, chromates, cyanides, ferrocyanides, fulminates, glycerides, halides, nitrates, nitrites, permanganates, perchlorates, picrates, sulphides, hydrogen peroxide, nitromethane, phosphorus, heat and moisture.
Hazardous decomposition products	Hazardous decomposition products formed under fire conditions. - Sulphur oxides.

SECTION 11 - TOXICOLOGICAL INFORMATION

SULFURIC ACID

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Severe burns and corrosion of ocular tissue that may lead to corneal ulceration and blindness.
- Skin	Severe burns and tissue ulcerations. May be fatal, if the extent of the burns is considerable.
- Inhalation	Spasms, irritation and inflammation of the nose, throat and lungs. Edema of the larynx and bronchi. Chemical pneumonitis and pulmonary edema that can lead to death.
Acute toxicity (Ingestion)	Corrosion and ulceration of the mouth, throat, esophagus, stomach and abdominal wall. Dysphagia, kidney damage, abdominal pain, cramps, diarrhea, melena, hematemesis, anuria, possible perforation of the esophagus and stomach, convulsions, salivation, stupor, circulatory collapse, unconsciousness, coma and can lead to death .
Chronic exposure effects / symptoms	Burning sensation, dermatitis and dyschromia, conjunctivitis, lung and eye damage, chest pain, digestive disorders, tooth abrasion, cough, dyspnea, laryngitis, emphysema, tracheobronchitis, headache, dizziness, fever, salivation tremors, paleness, muscle weakness, weight loss and loss of appetite, seizures, nausea and vomiting.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 2,140 mg/kg LD50 Dermal - Data not available.
CL50 (specify species and route of entry)	LC50 Inhalation - Mouse - 4h - 850 mg/m ³

FERROUS SULFATE HEPTAHYDRATE

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Irritation and may cause inflammation of the conjunctiva.
- Skin	Irritation and dermatitis.
- Inhalation	Irritation of the mucous membranes and respiratory tract. Nervous disorders, chest pain, cough, dyspnea, headache, dizziness, sweating, salivation, nausea and vomiting.
Acute toxicity (Ingestion)	Irritation and inflammation of the mucous membranes. Abdominal pain, liver damage, cramps, diarrhea, headache, dizziness, acidosis, sweating, salivation, tachycardia, seizures, nausea and vomiting. NOTE: Ingestion of less than 5 grams, especially in children, may result in bloody diarrhea and vomiting, liver problems, tachycardia, severe dehydration and even peripheral vascular collapse which may be fatal.
Chronic exposure effects / symptoms	Burning sensation, dermatitis, conjunctivitis, nervous disorders, chest pain, cough, dyspnea, laryngitis, headache, dizziness, confusion, irritability, sweating, salivation, paleness, weakness, nausea and vomiting.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 591 mg/kg LD50 Dermal - Rat - 1632 mg/kg
CL50 (specify species and route of entry)	Data not available.

SUMMARY

Acute exposure effects / Symptoms:	By exposure routes below.
Ingestion	To our knowledge, the product has not been fully evaluated
Inhalation	To our knowledge, the product has not been fully evaluated
Skin	To our knowledge, the product has not been fully evaluated
Eyes	To our knowledge, the product has not been fully evaluated
Chronic exposure effects / Symptoms:	To our knowledge, the product has not been fully evaluated
ETA Mix (Estimated Acute Toxicity)	LD50 Oral: > 5000 mg/kg - Rat LD50 Dermal: > 5000 mg/kg - Rat LC50 Inhalation: 18 280 mg/m ³ - 4h - Mouse

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity	Sulfuric acid: Toxicity to fish: LC50 - Gambusia affinis (Mosquito fish) - 42 mg/l - 96 h Toxicity to daphnia and other aquatic invertebrates: EC50 - Daphnia magna (Water flea) - 29 mg/l - 24 h
Persistence and degradability	Data not available.
Bioaccumulative potential	Data not available.
Mobility in soil	Data not available.
Other adverse effects	Data not available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of contents / container in accordance with local / regional / national / international regulations / or contact a specialist waste disposal company.
Contaminated Packaging	Dispose of as unused product.

SECTION 14 - TRANSPORT INFORMATION

UN Number	3264
UN Proper shipping name	LIQUIDE INORGANIQUE CORROSIF, ACIDE, N.S.A (acide sulfurique)
Transport hazard class(es)	8 Corrosive substances
Packing group	II
Limited quantity index	1L
ERAP Index	-
Special precautions	16

SECTION 15 - REGULATORY INFORMATION

WHIMS CANADA	Corrosive to metals-Category 1 Serious eye damage/eye irritation - Serious eye damage category 1 Skin corrosion/irritation - Skin corrosion category 1
---------------------	--

SECTION 16 - OTHER INFORMATION

Further information

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Last Update: 2/3/2020