



Centre Anti-Poison pour le Québec: (800) 463-5060

Tél. (Qc): (418) 660-8666 / 800-890-8666


Fax. (Qc): (418) 660-8998

SAFETY DATA SHEET

SECTION 01 - PRODUCT AND COMPANY IDENTIFICATION

Product Identifier HEPTANE		Product Use Laboratory use	
Chemical formula CH ₃ (CH ₂) ₅ CH ₃		Product code HP-0101; HR-0901	Molar weight 100,21
Chemical name / Commercial name / Synonymous HEPTANE NORMAL, n-HEPTANE, MÉTHANE DE DIPROPYLE, HYDRURE D'HEPTYLE, GETTYSOLVE-C			
Supplier's name Laboratoire MAT		Address-Street 610, Adanac Street	
City Québec		Province Québec	
Postal code G1C 7B7	Internet www.labmat.com	Phone number 418-660-8666 / 800-890-8666	
Emergency phone	CANUTEC: 613-996-6666 CENTRE ANTI-POISON DU QUÉBEC 800-463-5060		
Date SDS 12/27/2018	SDS Prepared by Laboratoire MAT	E-Mail labmat@labmat.com	

SECTION 02 - HAZARDS IDENTIFICATION

Classification WHIMS / GHS	Flammable liquids category 2 Skin corrosion/irritation - Skin irritation category 2 Specific target organ toxicity - Single exposure category 3 Aspiration hazard category 1	
Signal Word	DANGER	
Hazards statements (H)	H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness.	
Precautionary statements (P)	P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust / fume / gas / mist / vapours / spray. P264 Wash the areas of the body that have been in contact with the product after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection. P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P312 Call a POISON CENTER or doctor/physician if you feel unwell. P321 Specific treatment (see section 4 of the SDS and on this label). P331 Do NOT induce vomiting. P332 + P313 If skin irritation occurs: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P370 + P378 In case of fire: Use water spray or alcohol-resistant foam, or dry powder or carbon dioxide for extinction. P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/container in accordance with local / regional / national / international regulations or contact a specialist waste disposal company.	
PICTOGRAMS		
Other dangers	NFPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Significant; 4=Extreme)	
	Health 1 Fire 4 Reactivity 0 Special danger	

SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingrédients (Dénomination chimique / synonymes)	Numéro CAS et tout identificateur unique	Concentration (%)
Heptane	142-82-5	<=100

SECTION 04 - FIRST AID MEASURES

Eye contact	Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes. If irritation persists, seek medical attention.
Skin contact	Wash skin with plenty of water for at least 15 minutes. Remove soiled clothing. If irritation persists, seek medical attention.
Inhalation	Move the unwell person to the fresh air. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	If the person is conscious, give water to drink. Never give anything by mouth to an unconscious person. Consult a physician.
Most important symptoms and effects (acute and delayed)	Ref. section 11.
Immediate medical attention and special treatment, if necessary	In case of medical consultation, keep this sheet available.
General advice	Show this safety data sheet to the doctor in attendance.

SECTION 05 - FIREFIGHTING MEASURES

Flammability	Yes
Ignition conditions	Strong oxidizing agents, heat, sparks and open flame. Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.
Suitable extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	Do not use a jet of water.
Hazardous combustion / decomposition products	Hazardous decomposition products formed under fire conditions. Carbon oxides.
Special fire and explosion hazards	The return flame distance can be considerable. Violent reaction with phosphorous + chlorine. May react violently with incompatible products (Ref Section 10).
Special protective equipment and precautions for firefighters	Discard incompatible substances if this can be done without risk. Firefighters should be equipped with standard protective equipment, fireproof clothing, face mask, gloves, protective boots and, where appropriate, self-contained breathing apparatus.

SECTION 06 - ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up / Personnel precautions, protective equipment	Evacuate personnel to safe areas. Cut off all sources of ignition. Absorb the product with sand or vermiculite. Dilute residues with water, clean and rinse. Ensure a good ventilation of the premises. Dispose of residues in a container for disposal of hazardous materials. When handling, wear suitable safety equipment. Use breathing apparatus if necessary. Avoid breathing vapours, mist or gas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not let product enter drains.
--	---

SECTION 07 - HANDLING AND STORAGE

Conditions for safe storage	Store in a cool, dry place. Keep container tightly closed and store away from strong oxidants, heat, sparks and open flame. Use venting and electrical equipment that is grounded and does not produce ignition sources (sparks). Protect from the sun's rays. Store under inert gas. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Methods of handling	Always open containers slowly to allow any excess pressure to vent. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Heptane	142-82-5	TWA	400.000000 ppm	Canada. British Columbia OEL
		STEL	500.000000 ppm	Canada. British Columbia OEL
		TWAEV	400.000000 ppm 1,635.000000 mg/m3	Canada. Ontario OELs
		STEV	500.000000 ppm 2,045.000000 mg/m3	Canada. Ontario OELs
		TWAEV	400.000000 ppm 1,640.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEV	500.000000 ppm 2,050.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	400.000000 ppm 1,640.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEL	500.000000 ppm 2,050.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	400.000000 ppm 1,640.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEL	500.000000 ppm 2,050.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	400.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	500.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		TWA	400.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	500.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)

Data source	Sigma-Aldrich (Millipore Sigma)
Ventilation	Fan.
Respiratory	If work under the hood is not possible, or if the permissible levels are exceeded, use a mechanical filter / cartridge against NIOSH vapors or a respirator with air supply.
Gloves	Handle with gloves.
Eyes	Safety goggles with safety shutters.
Shoes	Safety shoes.
Clothing	Labcoat.
Engineering control	Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid.
Appearance	Liquide incolore-
Odour	Sucré, faible odeur d'essence.
Odour threshold	Data not available
pH	Donnée non disponible.
Melting point / Freezing point	-91°C
Initial boiling point	98°C
Boiling range	Data not available
Flash point	-1°C
Evaporation rate	-
Flammability	Yes
Lower flammable / Explosive limit	1%
Upper flammable / Explosive limit	7%
Vapour pressure	60.9 hPa @ 25 °C-
Vapour density	3.45 (Air=1)-
Relative density	0.684g/ml
Solubility	Insoluble dans l'eau 3.4 mg/L à 25°C. Miscible avec l'alcool, le chloroforme et l'éther.
Partition coefficient water/n-octanol	log Kow = 4.66-
Auto-ignition temperature	204°C
Decomposition temperature	Data not available
Viscosity	Data not available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	Non-reactive under normal conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Vapours may form explosive mixture with air.
Conditions of instability (Including sensitivity to shock / static discharge / vibration)	Avoid excessive heat. Avoid the accumulation of static electricity.
Incompatible material	Strong oxidants.
Hazardous decomposition products	Toxic vapors of carbon monoxide and dioxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

HEPTANE

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Irritation and tearing.
- Skin	Irritation and dermatitis.
- Inhalation	Irritation of the mucous membranes and respiratory tract. Narcotic effects, cough, dyspnea, headache, dizziness, drowsiness, incoordination, erythema and may lead to unconsciousness. Inhalation of very high concentrations may cause tracheobronchial irritation, convulsions, narcosis and coma.
Acute toxicity (Ingestion)	Irritation of the mucous membranes. Narcotic effects, gastrointestinal disorders, cramps, diarrhea, headache, dizziness, drowsiness, hallucinations, incoordination, erythema, nausea and vomiting, convulsions and may result in unconsciousness and coma.NOTE: aspiration of the product into the lungs can cause chemical pneumonia.
Chronic exposure effects / symptoms	Burning sensation, dermatosis (degreasing action), narcotic effects, chest pain, cough, dyspnea, headache, dizziness, drowsiness, incoordination, irritability, erythema, fatigue, loss of appetite, nausea and vomiting.
DL50 (specify species and route of entry)	LD50 Oral - Rat - >15 g/kg LD50 Dermal - Rabbit - > 2 g/kg
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 4h - 103 000 mg/m3

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity	Toxicity to fish: CL50 - Carassius auratus (Gold fish) - 4 mg/L - 24h CL50 - Tilapia mossambica - 375 mg/L - 96h Toxicity to daphnia and other aquatic invertebrates: EC50 - Daphnia magna (Water flea) - 1.50 mg/L - 48h
Persistence and degradability	Data not available.
Bioaccumulative potential	Indication of bioaccumulation.
Mobility in soil	Data not available.
Other adverse effects	Harmful to aquatic life with long lasting effects. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of contents / container in accordance with local / regional / national / international regulations / or contact a specialist waste disposal company.
Contaminated Packaging	Dispose of as unused product.

SECTION 14 - TRANSPORT INFORMATION

UN Number	1206
UN Proper shipping name	HEPTANES
Transport hazard class(es)	3 Flammable liquids
Packing group	II
Limited quantity index	1L
ERAP Index	-
Special precautions	-

SECTION 15 - REGULATORY INFORMATION

WHIMS CANADA	Flammable liquids category 2 Skin corrosion/irritation - Skin irritation category 2 Specific target organ toxicity - Single exposure category 3 Aspiration hazard category 1
---------------------	---

SECTION 16 - OTHER INFORMATION

Further information

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Last Update: 12/27/2018