SAFETY DATA SHEET

SECTION 01 - IDENTIFICATION

Product Identifier	POTASSIUM HYDROXIDE 10%W/V in GLYCERIN 10%V/V
Other identification (Chemical name, Commercial name, Synonymous)	-
Product code	PS-1367
Chemical formula	Mélange
Molar weight	
Recommended use and Restrictions on use	For laboratory, school, commercial or industrial use. Not for medical or household use. Do not use for medical, food or household purposes.
Supplier	LABORATOIRE MAT 610, rue Adanac Québec Québec G1C 7B7 418-660-8666 Mon-Fri 8h-16h www.labmat.com labmat@labmat.com
Emergency phone	418-660-8666 Mon-Fri 8h-16h CENTRE ANTI-POISON DU QUÉBEC 800-463-5060
Date SDS	2025-07-09

SECTION 02 - HAZARDS IDENTIFICATION

WHIMS CANADA

- Skin corrosion/irritation - Skin corrosion - category 1
- Serious eye damage/eye irritation - Eye irritation - category 1

PICTOGRAMS



Signal Word

DANGER

Hazards statements (H)

- Causes severe skin burns and eye damage
- Causes serious eye damage

Precautionary statements (P)

- Do not breathe mists, gases, vapors and other fumes, or the product itself.
- Wear protective gloves (nitrile, butyl, neoprene), protective clothing and eye and face protection.
- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse with water.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- Immediately call a POISON CENTER or a physician.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Store locked up.
- Dispose of contents and container in accordance with local, regional and national regulations, or contact a specialist waste disposal company.

Other dangers

NFPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Signifiant; 4=Extreme)

Health	1
Fire	0
Reactivity	0
Special danger	

SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS

Component	No. CAS	% Weight
Potassium hydroxide	1310-58-3	7%
Glycerin	56-81-5	11%
Water	7732-18-5	Balance

SECTION 04 - FIRST AID MEASURE

Eye contact

Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes. If irritation persists, seek medical attention.

Skin contact

Wash skin with plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation persists, seek medical attention.

Inhalation

Move the unwell person to the fresh air. If breathing is difficult, give oxygen. Consult a physician.

Ingestion

If the person is conscious, give water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.

Most important symptoms and effects (acute and delayed)

When concentrated, high exposure to the products causes the following main symptoms: Chemical burns of the skin, eyes and respiratory and digestive mucous membranes. Skin, eye and respiratory system irritation. Abdominal pain. The corrosive effect will outweigh the toxicity for the concentrated product. Ref. section 11.

Immediate medical attention and special treatment, if necessary

Treat according to symptoms. Show this sheet to the attending physician.

SECTION 05 - FIREFIGHTING MEASURES

Suitable extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	Data not available.
Combustion products	Hazardous combustion products formed under fire conditions: Carbon oxides. Potassium oxides.
Specific hazards of the dangerous product	May react violently with incompatible products (Ref Section 10).
Special protective equipment and precautions for firefighters	Discard incompatible substances if this can be done without risk. Firefighters should be equipped with standard protective equipment, fireproof clothing, face mask, gloves, protective boots and, where appropriate, self-contained breathing apparatus.

SECTION 06 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency measures	Evacuate personnel to safe areas. When handling, wear appropriate safety equipment (reference Section 8 for protective equipment to be used). Ensure a good ventilation. Use NIOSH cartridge respiratory protection if necessary or for larger spills. Avoid breathing in vapours, spray mists or gases.
Methods and materials for containment and cleaning up	Neutralize residues with dilute acid, then rinse with water. Dispose of residues in a container for disposal of hazardous materials. When handling, wear suitable safety equipment. Do NOT use absorbents composed with minerals, clay, or cellulose. Discharge into the environment must be avoided.

SECTION 07 - HANDLING AND STORAGE

Conditions for safe storage	Store in a cool, dry, and well-ventilated place. Keep container tightly closed and store away from heat, moisture, and incompatible products (ref. section 10).
Methods of handling	This product is corrosive to metals. Do not bottle in a metal container. Avoid contact withh eyes, skin and clothing. Avoid ingestion and inhalation. Wear personal protective equipment (ref. section 8) when handling. Always ensure good ventilation. Apply the usual standard hygiene rules: Wash your hands after use. Do not eat or drink during use.

SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION

WORKPLACE CONTROL PARAMETERS

Components	CAS-No.	Control parameters	Value	Basis
Potassium hydroxide	1310-58-3	C	2.000000 mg/m3	Canada. British Columbia OEL
		CEV	2.000000 mg/m3	Canada. Ontario OELs
		(c)	2.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required			
		C	2.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	A substance which may not be recirculated in accordance with section 108			
	A substance which may not be recirculated in accordance with section 108			
		C	2.000000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		C	2 mg/m3	USA. ACGIH Threshold Limit Values (TLV)

Components	CAS-No.	Control parameters	Value	Basis
Glycerin	56-81-5	TWA	10.000000 mg/m3 (total)	Canada. British Columbia OEL
		TWA	3.000000 mg/m3 (respirable)	Canada. British Columbia OEL
		TWA	10.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required			
		TWAEV	10 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	10.000000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)

Data origin	Sigma-Aldrich (Millipore Sigma) CNESST Worksafebc.com Alberta OELs.
Respiratory	If work under the hood is not possible, or if the permissible levels are exceeded, use NIOSH cartridge respiratory protection, or an air-supplied respirator.
Gloves	Gloves resistant to acidic corrosive materials. Suggested material: Nitrile. Butyl. Neoprene. The type, thickness and length of the glove must be chosen according to the use, the concentration of the product, as well as the duration of use. Replace gloves regularly for better protection.
Eyes	Safety goggles with safety shutters.
Shoes	Use safety shoes.
Clothes	Labcoat. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Engineering control	Use fan. Recirculation is prohibited. Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid
Color	Colorless
Odour	Data not available
Odour threshold	Data not available
Melting point and freezing point	Data not available
Boiling point	Data not available
Flammability	No
Lower flammable / Explosive limit	Data not available
Upper flammable / Explosive limit	Data not available
Flash point	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
pH	>12
Kinematic viscosity	Data not available
Solubility	Sol in water
Partition coefficient water/n-octanol	Data not available
Vapour pressure	Data not available
Relative density	Data not available
Vapour density	Data not available
Particle characteristics	Not applicable

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	Basic product, reacts violently with strong acids. May react violently with incompatible substances.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	May react violently with incompatible substances.
Conditions to avoid	Avoid moisture. Avoid contact with incompatible materials. Exposure to air.
Incompatible materials	When pure, the products react with the following products: Strong acids. Strong oxidizers. Acid chlorides. Acid anhydrides. Acrylonitrile. Acrolein. Alcohols. Aluminum. Copper. Stain. Magnesium. Halogenated organics. Organo-nitro compounds. Organic materials. Lead. Metal oxides. Chromic anhydride. Calcium hypochlorite. Phosphorus triiodide. Sodium hydride. Chlorides.
Hazardous decomposition products	Carbon oxides. Potassium oxides.

SECTION 11 - TOXICOLOGICAL INFORMATION

POTASSIUM HYDROXIDE 10%W/V IN GLYCERIN 10%V/V

Routes of exposure	Ingestion, inhalation, skin and eye contact. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.
Acute exposition effects / symptoms:	By exposure route below. The corrosive effect will outweigh the toxicity for the concentrated product.
- Eyes	May cause severe eye irritation. May cause: Inflammation of the conjunctiva. To our knowledge, the chemical, physical and toxicological properties have not been fully investigated.
- Skin	May cause: Irritation. Severe burns and tissue ulcerations. To our knowledge, the chemical, physical and toxicological properties have not been fully investigated.
- Inhalation	To our knowledge, the chemical, physical and toxicological properties have not been fully investigated.
Acute toxicity (Ingestion)	To our knowledge, the chemical, physical and toxicological properties have not been fully investigated.
Chronic exposure effects / symptoms	To our knowledge, the chemical, physical and toxicological properties have not been fully investigated.
DL50 (specify species and route of entry)	ETA Mix (Estimated Acute Toxicity): LD50 Oral - Rat - 3504mg/kg. LD50 Dermal - Rabbit - >5000mg/kg.
CL50 (specify species and route of entry)	ETA Mix (Estimated Acute Toxicity) LC50 Inhalation - Rat - 4 h - 52.2mg/L.

POTASSIUM HYDROXIDE

Routes of exposure	Ingestion, inhalation, skin and eye contact.
Acute exposition effects / symptoms:	By exposure route below. The corrosive effect will outweigh the toxicity for the concentrated product.
- Eyes	Causes serious eye damage.
- Skin	Severe burns and tissue ulcerations.
- Inhalation	Irritation and inflammation of the nose, throat and lungs. Spasms. Edema of the larynx and bronchi. Chemical pneumonitis. Pulmonary edema. Can lead to death.
Acute toxicity (Ingestion)	Burning of the mouth, throat, esophagus and abdominal wall. Dysphagia. Abdominal pain. Cramps. Diarrhea. Melena. Possible perforation of the esophagus and stomach. Bloody vomiting Tremors. Convulsions. Circulatory collapse. Stupor. Loss of consciousness. Coma. Possible death.
Chronic exposure effects / symptoms	Burning sensation. Dermatitis. Conjunctivitis. Lung damage. Nervous disorders. Chest pain. Cough. Dyspnoea. Laryngitis. Headache. Dizziness. Confusion. Irritability. Sweating. Salivation. Tearing. Fatigue. Alopecia. Weight loss. Loss of appetite. Nausea and vomiting. Convulsions. Target organs: Skin. Eyes. Respiratory system.
DL50 (specify species and route of entry)	LD50 Oral - 273 mg/kg. LD50 Dermal - Data not available.
CL50 (specify species and route of entry)	LC50 Inhalation - Data not available.

GLYCERIN (GLYCEROL)

Routes of exposure	Ingestion, inhalation, skin and eye contact.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Irritation. Inflammation of the conjunctiva.
- Skin	Irritation.
- Inhalation	Irritation of the mucous membranes and respiratory tract.
Acute toxicity (Ingestion)	Mucous membrane irritation. Gastrointestinal disorders. Cramps. Diarrhea. Headaches. Dizziness. Convulsions. Nausea and vomiting.
Chronic exposure effects / symptoms	Burning sensation. Conjunctivitis. Nervous disorders. Headache. Dizziness. Fatigue. Nausea and vomiting.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 12600mg/kg. LD50 Dermal - Rabbit - >10 000 mg/kg.
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 1 h - >570 mg/m3.

SECTION 12 - ECOLOGICAL INFORMATION

POTASSIUM HYDROXIDE 10%W/V IN GLYCERIN 10%V/V

Ecotoxicity	Data not available.
Persistence and degradability	Data not available.
Bioaccumulative potential	Data not available.
Mobility in soil	Probable mobility in the environment due to its solubility in water.
Other adverse effects	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

POTASSIUM HYDROXIDE

Ecotoxicity	Toxicity to fish: LC50 - Gambusia affinis (Mosquito fish) - 80 mg/L - 96 h.
Persistence and degradability	Not applicable for inorganic substances.
Bioaccumulative potential	Data not available.
Mobility in soil	Probable mobility in the environment due to its solubility in water.
Other adverse effects	Harmful to aquatic life. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

GLYCERIN (GLYCEROL)

Ecotoxicity	Toxicity to fish: LC50- Goldfish. >5000 mg/L 24h. Toxicity to daphnia and other aquatic invertebrates: LC50 - Daphnia magna (Water flea) - Static test - > 10,000 mg/l; 24 h.
Persistence and degradability	Data not available.
Bioaccumulative potential	Data not available.
Mobility in soil	Data not available.
Other adverse effects	Data not available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of contents and container in accordance with local, regional and national regulations, or contact a specialist waste disposal company.
Contaminated Packaging	Dispose of as unused product.

SECTION 14 - TRANSPORT INFORMATION

UN Number	1814
UN Proper shipping name	HYDROXYDE DE POTASSIUM EN SOLUTION
Transport hazard class(es)	Matières corrosives 8
Packing group	III
Limited quantity index	5 L
ERAP Index	-
Special precautions	-

SECTION 15 - REGULATORY INFORMATION

WHIMS CANADA	- Skin corrosion/irritation - Skin corrosion - category 1 - Serious eye damage/eye irritation - Eye irritation - category 1

SECTION 16 - OTHER INFORMATION

CNESST: Commission des normes, de l'équité et de la santé et sécurité au travail
NIH: National institute of health (U.S. Naltional Library of Medecine)
ECHA: Agence Européenne de Chimie
ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
VECD: Valeur d'exposition courte durée
VEMP: Valeur d'exposition moyenne pondérée
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TLV : Threshold limit value
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling
RSST: Règlement sur la santé et sécurité au travail (Québec)
INRS: l'Institut national de recherche et de sécurité pour la prévention des accidents du travail et des maladies professionnelles (France)

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

LAST UPDATE: 2025-07-09