




Centre Anti-Poison pour le Québec: (800) 463-5060
 Tél. (Qc): (418) 660-8666 / 800-890-8666
 Fax. (Qc): (418) 660-8998

SAFETY DATA SHEET

SECTION 01 - PRODUCT AND COMPANY IDENTIFICATION

Product Identifier CALCIUM SULFATE (ANHYDROUS)		Product Use Laboratory use	
Chemical formula CaSO ₄		Product code CR-0120; CT-0120; CF-0442	Molar weight 136,14
Chemical name / Commercial name / Synonymous CALCIUM SULFATE ANHYDROUS, ANHYDRITE, DRIERITE, SULFATE DE CHAUX ANHYDRE, GYPSE ANHYDRE, KARSTENITE, MURIACITE			
Supplier's name Laboratoire MAT		Address-Street 610, Adanac Street	
City Québec		Province Québec	
Postal code G1C 7B7	Internet www.labmat.com	Phone number 418-660-8666 / 800-890-8666	
Emergency phone	CANUTEC: 613-996-6666	CENTRE ANTI-POISON DU QUÉBEC 800-463-5060	
Date SDS 9/29/2020	SDS Prepared by Laboratoire MAT	E-Mail labmat@labmat.com	

SECTION 02 - HAZARDS IDENTIFICATION

Classification WHIMS / GHS	Not a hazardous substance according to WHMIS 2015
Other dangers	NFPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Signifiant; 4=Extreme)
	Health 1 Fire 0 Reactivity 0 Special danger

SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingrédients (Dénomination chimique / synonymes)	Numéro CAS et tout identificateur unique	Concentration (%)
Sulfate de calcium	7778-18-9	<=100

SECTION 04 - FIRST AID MEASURES

Eye contact	Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes. If irritation persists, seek medical attention.
Skin contact	Wash skin with plenty of water for at least 15 minutes. Remove soiled clothing. If irritation persists, seek medical attention.
Inhalation	Move the unwell person to the fresh air. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	If the person is conscious, rinse the mouth with water. Never give anything by mouth to an unconscious person. Consult a physician.
Most important symptoms and effects (acute and delayed)	Main symptoms of high exposure: Eyes irritation. Irritation of the respiratory system. Cough. Redness. Ref. section 11.
Immediate medical attention and special treatment, if necessary	In case of medical consultation, keep this sheet available.
General advice	Show this safety data sheet to the doctor in attendance.

SECTION 05 - FIREFIGHTING MEASURES

Flammability	No
Ignition conditions	Non flammable.
Suitable extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	Data not available.
Hazardous combustion products	Hazardous decomposition products formed under fire conditions. Calcium oxides. - Sulphur oxides
Special fire and explosion hazards	If heated, anhydrous calcium sulphate may react violently with aluminum, diazomethane and phosphorus. May react violently with incompatible products (Ref Section 10).
Special protective equipment and precautions for firefighters	Discard incompatible substances if this can be done without risk. Firefighters should be equipped with standard protective equipment, fireproof clothing, face mask, gloves, protective boots and, where appropriate, self-contained breathing apparatus.

SECTION 06 - ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up / Personnel precautions, protective equipment	Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment. Pick up with a shovel or broom, taking care not to scatter dust. Dispose of residues in a container provided for the disposal of hazardous materials. Do not let product enter drains.
----------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 07 - HANDLING AND STORAGE

Conditions for safe storage	Hygroscopic. Keep container tightly closed in a dry and well-ventilated place. Store in cool place. Keep container tightly closed and store away from heat, water, moisture, and incompatible products.
Methods of handling	Avoid contact with the skin, eyes and clothes. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust or vapor is formed. Wear personal protective equipment when handling. Always ensure good ventilation. Transport according to TDG (ref Section 14)

SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Calcium sulfate (anhydrous)	7778-18-9	TWA	10.000000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		TWAEV	5 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
Remarks	The standard corresponds to dust containing no asbestos and the percentage in crystalline silica is less than 1 %.			
		TWAEV	5.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	The standard corresponds to dust containing no asbestos and the percentage in crystalline silica is less than 1 %.			
		TWA	10.000000 mg/m3	Canada. British Columbia OEL
	The 8-hour TWA listed in the Table is for the total dust. The substance also has an 8-hour TWA of			
		TWAEV	10.000000 mg/m3	Canada. Ontario OELs
		TWAEV	10 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	The standard corresponds to dust containing no asbestos and the percentage in crystalline silica is less than 1 %.			
		TWAEV	10.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	The standard corresponds to dust containing no asbestos and the percentage in crystalline silica is less than 1 %.			
		TWA	10.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWAEV	10.000000 mg/m3	Canada. Ontario OELs
		TWA	10.000000 mg/m3	Canada. British Columbia OEL
		TWA	10.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWAEV	5.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	The standard corresponds to dust containing no asbestos and the percentage in crystalline silica is less than 1 %.			
		TWAEV	10.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	The standard corresponds to dust containing no asbestos and the percentage in crystalline silica is less than 1 %.			
		TWA	10.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
	TWA 10 mg/m3 Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)			
		TWA	10.000000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		TWA	10.000000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		TWA	10 mg/m3	USA. ACGIH Threshold Limit Values (TLV)

Data source	Sigma-Aldrich.
Ventilation	Fan.
Respiratory	If the permissible levels are exceeded, use a mechanical filter / cartridge against NIOSH vapors or a respirator with air supply.
Gloves	Handle with gloves.

Eyes	Safety goggles with safety shutters.
Shoes	Use safety shoes.
Clothing	Labcoat. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Engineering control	Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Solid.
Appearance	Granulé beige.
Odour	inodore.
Odour threshold	Data not available
pH	Donnée non disponible..
Melting point / Freezing point	1450°C
Initial boiling point	Data not available
Boiling range	Data not available
Flash point	Data not available
Evaporation rate	Data not available
Flammability	No
Lower flammable / Explosive limit	Data not available
Upper flammable / Explosive limit	Data not available
Vapour pressure	Data not available
Vapour density	Data not available
Relative density	2.96g/cm ³
Solubility	Peu soluble dans l'eau 2.4 g/l à 20 °C.
Partition coefficient water/n-octanol	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Viscosity	Data not available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	Usually not very reactive but can act as an oxidant.
Chemical stability	Stable under recommended storage conditions. Hygroscopic.
Possibility of hazardous reactions	Stable under normal conditions.
Conditions of instability (Including sensitivity to shock / static discharge / vibration)	This product quickly absorbs moisture from the air.
Incompatible material	Reducing agents. Strong acid. Diazomethane. Aluminum. Hydrogen peroxide Phosphorus. Alcohols. Ethers. Halogenated compounds. Magnesium, Alkaline.
Hazardous decomposition products	Hazardous decomposition products formed under fire conditions. - Sulphur oxides. - Calcium oxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

CALCIUM SULFATE (ANHYDROUS)

Routes of exposure	Inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Irritation and tearing. Redness.
- Skin	Irritation and dermatitis.
- Inhalation	Irritation of the mucous membranes and respiratory tract. Nervous disorders, chest pain, cough, dyspnea, headache, dizziness, nausea and vomiting. Rhinitis. Epistaxis (nosebleed).
Acute toxicity (Ingestion)	Irritation of the mucous membranes. Gastrointestinal disorders, cramps, diarrhea, headache, dizziness, convulsions, nausea and vomiting.
Chronic exposure effects / symptoms	Burning sensation, dermatitis, nervous disorders, chest pain, cough, dyspnea, headache, dizziness, confusion, irritability, tearing, tiredness, nausea and vomiting. NOTE: Prolonged inhalation of dust may cause severe irritation of the respiratory tract.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 3 000 mg/kg. LD50 Dermal - Data not available.
CL50 (specify species and route of entry)	CL50 inhalation - Rat Male et female - 3.26 mg/L - 4 h.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity	LC50 - Lepomis macrochirus - 2980 mg/L - 96 h .
Persistence and degradability	Data not available.
Bioaccumulative potential	Data not available.
Mobility in soil	Unlikely mobility in the environment due to its low solubility in water.
Other adverse effects	Data not available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of contents / container in accordance with local / regional / national / international regulations / or contact a specialist waste disposal company.
Contaminated Packaging	Dispose of as unused product.

SECTION 14 - TRANSPORT INFORMATION

UN Number	N/R
UN Proper shipping name	
Transport hazard class(es)	
Packing group	
Limited quantity index	
ERAP Index	
Special precautions	

SECTION 15 - REGULATORY INFORMATION

WHIMS CANADA	Not a hazardous substance according to WHMIS 2015
---------------------	---------------------------------------------------

SECTION 16 - OTHER INFORMATION

Further information

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Last Update: 9/29/2020