

Centre Anti-Poison pour le Québec: (800) 463-5060 Tél. (Qc): (418) 660-8666 / 800-890-8666 Fax. (Qc): (418) 660-8998

### SAFETY DATA SHEET

## **SECTION 01 - PRODUCT AND COMPANY IDENTIFICATION**

Product Identifier				Product Use	
PHENOLPHTALEIN 1% (IN 70% ETHANOL)				Laboratory use	
Chemical formula				Product code	Molar weight
-				PS-0924; PS-0470	
Chemical name / Commercial name /	/ Synonymous				
-					
Supplier's name			Address-Street		
Laboratoire MAT		610, Adanac Street			
City		Province			
Québec			Québec		
Postal code Internet			Phone number	Phone number	
G1C 7B7 www.labmat.com		418-660-8666 / 800-890-8666			
Emergency phone CANUTEC: 613-996-6666		CENTRE ANTI-POISON DU QUÉBEC 800-463-5060		3-5060	
Date SDS SDS Prepared by		SDS Prepared by	•	E-Mail	
1/28/2019 Laboratoire MA		T	labmat@labmat.com		

## **SECTION 02 - HAZARDS IDENTIFICATION**

Classification WHIMS / GHS	Flammable liquids	category 2
	Carcinogenicity ca	tegory 1B
	Reproductive toxic	city category 2
	'	rgan Toxicity - Single exposure category 1
	Serious eye dama	ge/eye irritation - Eye irritation category 2
Signal Word	DANGER	
Hazards statements (H)	H225 Highly flam	mable liquid and vapour.
	H319 Causes serio	ous eye irritation.
	H350 May cause	
	H361 Suspected of	of damaging fertility or the unborn child.
	H370 Causes dam	age to organs
Precautionary statements (P)	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
	P233	Keep container tightly closed.
	P240	Ground/bond container and receiving equipment.
	P241	Use explosion-proof electrical/ventilating/lighting equipment.
	P242	Use only non-sparking tools.
	P243	Take precautionary measures against static discharge.
	P260	Do not breathe dust / fume / gas / mist / vapours / spray.
	P264	Wash the areas of the body that have been in contact with the product after handling.
	P270	Do no eat, drink or smoke when using this product.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P303 + P361 + P	353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P305 + P351 + P	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P308 + P311	IF exposed or concerned: Call a POISON CENTER or a doctor.
	P308 + P313	IF exposed or concerned: Get medical advice/attention.
	P321	Specific treatment (see section 4 of the SDS and on this label).
	P337 + P313	If eye irritation persists: Get medical advice/attention.
	P370 + P378	In case of fire: Use water spray or alcohol-resistant foam, or dry powder or carbon dioxide for extinction.
	P403 + P235	Store in a well-ventilated place. Keep cool.
	P405	Store locked up.
	P501	Dispose of contents/container in accordance with local / regional / national / international regulations or contact a specialist waste disposal company.
PICTOGRAMS	<u>i</u>	
Other dangers	N	FPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Signifiant; 4=Extreme)
	Health 2	· · · · · · · · · · · · · · · · · · ·
	Fire 4	
	Reactivity 0	
	Special danger	

## **SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS**

Ingrédients (Dénomination chimique / synonymes)	Numéro CAS et tout identificateur unique	Concentration (%)
Éthanol	64-17-5	54
Méthanol	67-56-1	9
Acétate d'éthyle	141-78-6	0.6
Phénolphtaléine	77-09-8	1
Eau	7732-18-5	Balance

#### **SECTION 04 - FIRST AID MEASURES**

Eye contact	Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes.
Skin contact	Wash skin with plenty of water for at least 15 minutes. Remove soiled clothing. If irritation persists, seek medical attention.
Inhalation	If breathed in, move person into fresh air. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	If the person is conscious, give water to drink. Never give anything by mouth to an unconscious person. Consult a physician.
Most important symptoms and effects (acute and delayed)	Ref. section 11.
Immediate medical attention and special treatment, if necessary	In case of medical consultation, keep this sheet available.
General advice	Show this safety data sheet to the doctor in attendance.

#### **SECTION 05 - FIREFIGHTING MEASURES**

Flammability	Yes
Ignition conditions	Strong oxidizing agents, heat, sparks and open flame. Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface.
Suitable extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	Do not use a heavy water stream.
Hazardous combustion / decomposition products	Hazardous decomposition products formed under fire conditions. Carbon oxides.
Special fire and explosion hazards	May react violently with incompatible products (Ref Section 10).
Special protective equipment and precautions for firefighters	Discard incompatible substances if this can be done without risk. Firefighters should be equipped with standard protective equipment, fireproof clothing, face mask, gloves, protective boots and, where appropriate, self-contained breathing apparatus.

### **SECTION 06 - ACCIDENTAL RELEASE MEASURES**

	Evacuate personnel to safe areas. Cut off all sources of ignition. Absorb the product with sand or
	vermiculite. Dilute residues with water, clean and rinse. Ensure a good ventilation of the premises. Dispose
Personnal precautions, protective	of residues in a container for disposal of hazardous materials. When handling, wear suitable safety
equipment	equipment. Use breathing apparatus if necessary. Avoid breathing vapours, mist or gas. Beware of
	vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not let
	product enter drains.

### **SECTION 07 - HANDLING AND STORAGE**

	Store in a cool, dry place. Protect from the sun's rays. Keep container tightly closed and store away from heat, water, moisture, and incompatible products. Use venting and electrical equipment that is grounded and does not produce ignition sources (sparks).
Methods of handling	Always open containers slowly to allow any excess pressure to vent. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

# **SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Ethanol	64-17-5	TWAEV	1000 ppm 1900 mg/m3	Canada. Ontario OELs
		TWA	1000 ppm 1880mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		VEMP	1000 ppm 1880mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEL	1000 ppm	Canada. British Columbia OEL
		TWA	1000 ppm	Canada. British Columbia OEL
Components	CAS-No.	Value	Control parameters	Basis
Methanol	67-56-1	TWA	200.000000 ppm 262.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Substance m	ay be readil	y absorbed through	intact skin
	STEL	_		
	250.000000	)		
	ppm 328.000000 mg/m3	)		
	Code (table	2: OEL)	ational Health and S	<u> </u>
	Substance m		y absorbed through	
		TWA	200.000000 ppm	Canada. British Columbia OEL
	Contributes	significantly t	o the overall expos	ure by the skin route.
		STEL	250.000000 ppm	Canada. British Columbia OEL
	Contributes	significantly t	o the overall expos	ure by the skin route.
		TWAEV	200.000000 ppm 262.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	Skin (percut	aneous)	1 3/	
		STEV	250.000000 ppm 328.000000	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	Claire (re-e-re-e-t		mg/m3	
	Skin (percut	TWA	200.000000	USA. ACGIH Threshold Limit Values (TLV)
		STEL	ppm 250.000000	USA. ACGIH Threshold Limit Values (TLV)
Components	CAS-No.	Value	Control Control	Basis
Components	CA3-NO.	value	parameters	pusis
Ethyl acetate	141-78-6	TWA	400.000000 ppm 1,440.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks			sure limit is based on irritation effects and its adjustment to compensate for ules is not required	
		TWA	150.000000 ppm	Canada. British Columbia OEL
		TWAEV	400.000000 ppm 1,440.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	400.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
Phenolphthalein	77-09-7	-	Data non available	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure

	,	,	•	
values	for	airborne	contaminants	

Data source	Sigma-Aldrich (Millipore Sigma)
Ventilation	Fan.
Respiratory	If the permissible levels are exceeded, use a mechanical filter / cartridge against NIOSH vapors or a respirator with air supply.
Gloves	Handle with gloves.
Eyes	Safety goggles with safety shutters.
Shoes	Safety shoes.
Clothing	Labcoat.
Engineering control	Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

### **SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES**

Physical state	Liquid.
Appearance	incolore-
Odour	Donnée non disponible.
Odour threshold	Data not available
pH	4-5.
Melting point / Freezing point	Data not available
Initial boiling point	Data not available
Boiling range	Data not available
Flash point	20-30 (estimé)°C
Evaporation rate	Data not available
Flammability	Yes
Lower flammable / Explosive limit	Data not available
Upper flammable / Explosive limit	Data not available
Vapour pressure	Data not available
Solubility	Miscible avec l'eau, les alcools et l'éther, acétone.
Vapour density	Data not available
Relative density	0.840g/ml
Partition coefficient water/n-octanol	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Viscosity	Data not available

### **SECTION 10 - STABILITY AND REACTIVITY**

Reactivity	Non-reactive under normal conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Stable under normal conditions. Vapours may form explosive mixture with air.
Conditions of instability (Including sensitivity to shock / static discharge / vibration)	Avoid contact with incompatible materials and extreme temperatures. Heat, flames, sparks.
Incompatible material	When pure, the products react with the following products: Acids, Oxidants, Acid Chlorides, Acid Anhydrides, Alkali Metals, Reducing Agents.
Hazardous decomposition products	Hazardous decomposition products formed under fire conditions. Carbon oxides.

### **SECTION 11 - TOXICOLOGICAL INFORMATION**

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	May cause eye irritation.
- Skin	May be harmful if absorbed through skin. May cause skin irritation.
- Inhalation	May be harmful if inhaled. Nervous disorders, dizziness, cough, dyspnea, headache, convulsions, nausea and vomiting. May cause respiratory tract irritation.
Acute toxicity (Ingestion)	May be harmful if swallowed. Abdominal discomfort, diarrhea, nausea, decreased blood pressure, weakness, pink staining of urine and feces. Nervous disorders, gastrointestinal disorders, rash, cramps, colitis, diarrhea, dizziness, headache, convulsions, nausea and vomiting.
Chronic exposure effects / symptoms	Long-term exposure may cause: abdominal pain, diarrhea, vomiting, electrolyte imbalance, dehydration, malabsorption, steatorrhea, weight loss, polydipsia, polyuria, cardiac arrhythmia, muscle weakness, prostration and histopathological lesions and kidney disorders. Is recognized as a possible carcinogen (class 2B) by IARC.
DL50 (specify species and route of entry)	Data not available.
CL50 (specify species and route of entry)	Data not available.
Routes of exposure	Ingestion.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Irritation and tearing.
- Skin	May cause skin irritation.
- Inhalation	May cause respiratory tract irritation.
Acute toxicity (Ingestion)	Euphoria, a feeling of intoxication, followed by central nervous system depression, which may include headache, nausea, dizziness, incoordination, speech disturbance, mental confusion and of narcosis.
Chronic exposure effects / symptoms	Cirrhosis of the liver and various diseases affecting the gastrointestinal, cardiovascular, nervous, hematological and respiratory systems.
DL50 (specify species and route of entry)	LD50 Oral - Rat - $7000 \mathrm{mg/kg}$ LD50 Dermal - Rabbit - $> 2,\!000 \mathrm{mg/kg}$
CL50 (specify species and route of entry)	LC50 Inhalation - Mouse - 1h - 60000 ppm.

## **METHANOL**

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	May cause eye irritation.
- Skin	Irritation and dermatitis.
- Inhalation	Irritation of the mucous membranes and respiratory tract. Narcotic effects, chest pain, cough, dyspnea, headache, dizziness, watery eyes, paresthesia, nystagmus, drowsiness, confusion, nausea and vomiting.
Acute toxicity (Ingestion)	Irritation of the mucous membranes. Narcotic effects, liver, kidney and eye damage, abdominal pain, cramps, diarrhea, headache, dizziness, paresthesia, nystagmus, drowsiness, incoordination, acidosis, nausea and vomiting, seizures, hypotension, respiratory collapse, loss of consciousness, coma and can lead to death. Acute absorption of methanol can cause blindness. Damage to: liver, kidneys, eyes, heart, central nervous system.
Chronic exposure effects / symptoms	Headache, dizziness, nausea, visual disturbances, decreased visual acuity, liver and kidney damage.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 1187 mg/kg LD50 Dermal - Lapin-15840 mg/kg
CL50 (specify species and route of entry)	LC50 Inhalation - Rat: 64000 ppm/4 h. LC50 Inhalation - Rat 115.9-130.7mg/L air / 4h.

#### **ETHYL ACETATE**

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Irritation and conjunctivitis. May cause opacification of the cornea.
- Skin	Irritation and dermatitis.
- Inhalation	Irritation of the mucous membranes and respiratory tract. Narcotic effects, cough, dyspnea, headache, dizziness, drowsiness, paresthesia, nystagmus, nausea and vomiting, convulsions and may result in unconsciousness.
Acute toxicity (Ingestion)	Irritation of the mucous membranes. Narcotic effects, liver and kidney damage, gastrointestinal disorders, cramps, diarrhea, headache, dizziness, drowsiness, tremors, convulsions, nausea and vomiting.
Chronic exposure effects / symptoms	Chronic poisoning can result in anemia and the appearance of leukocytosis. Burning sensation, dermatitis, conjunctivitis, narcotic effects, liver and kidney damage, chest pain, cough, dyspnea, laryngitis, headache, dizziness, somnolence, paresthesia, nystagmus, muscle weakness, weight loss, and loss of weight. appetite, nausea and vomiting.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 5620 mg/kg LD50 Dermal - Rabbit - > 2000 mg/kg
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 4h - 4000 ppm. LC50 Inhalation - Mouse - 4h - 1500 ppm

#### **SUMMARY**

Acute exposure effects / Symptoms:	By exposure routes below.
Ingestion	To our knowledge, the product has not been fully evaluated
Inhalation	To our knowledge, the product has not been fully evaluated
Skin	To our knowledge, the product has not been fully evaluated
Eyes	To our knowledge, the product has not been fully evaluated
Chronic exposure effects:	To our knowledge, the product has not been fully evaluated
	LD50 Oral : 6491 mg/kg - Rat LD50 Dermal : Data not available LC50 Inhalation : 41955 ppm - 4h - Rat

### **SECTION 12 - ECOLOGICAL INFORMATION**

Available ecological information	No.

#### **SECTION 13 - DISPOSAL CONSIDERATIONS**

	Dispose of contents / container in accordance with local / regional / national / international regulations / or contact a specialist waste disposal company.
Contaminated Packaging	Dispose of as unused product.

### **SECTION 14 - TRANSPORT INFORMATION**

UN Number	1987
UN Proper shipping name	ALCOOLS, N.S.A (éthanol, méthanol)
Transport hazard class(es)	3 Flammable liquids
Packing group	
Limited quantity index	1L
ERAP Index	-
Special precautions	16, 150

### **SECTION 15 - REGULATORY INFORMATION**

WHIMS CANADA	Flammable liquids category 2
	Carcinogenicity category 1B
	Reproductive toxicity category 2
	Specific Target Organ Toxicity - Single exposure category 1
	Serious eye damage/eye irritation - Eye irritation category 2

#### **SECTION 16 - OTHER INFORMATION**

#### **Further information**

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Last Update: 1/28/2019